

RG59 E64+VDE COAXIAL CABLE

APPLICATION


❖ High quality RG Type Coaxial cable,75 Ohm suitable for many applications, particularly broadcast and CCTV installations.

PRODUCT FACTS

- ❖ INDOOR USE, Accepts 100m longer (signal cable with DC power)
- ❖ Suitable for shop-lot, home
- ❖ 2core power 30x0.15mm

PRODUCT CODE

- ❖ RG59-ALL-C64FTC-100M
- ❖ RG59-ALL-C64FTC-250M TECHNICAL DATA



ITEM		UNIT	SPEC. VALUE
Inner Conductor	Material		Copper clad steel
	Dia.(approx)	mm	0.81 ± 0.15
Insulation	Material		Foam Polyethylene
	Nom. Thickness	mm	1.56 ± 0.18
	Dia.(approx)	mm	3.70 ± 0.18
	Colour		Natural
Outer Conductor	Type		Braid
	Material		Copper clad Aluminum
	Coverage	%	83 ± 3
	Dia.(approx)	mm	0.12 x 64
Jacket	Material		PVC
	Nom. Thickness	mm	0.80 ± 0.2
	Colour		Black
	Dia.(approx)	mm	5.90 ± 0.20
CHARACTERISTICS			
DC Conductor Resistance at 20°C			$<26.1\Omega/100m$
Insulation Resistance at 20°C			$> 200 \text{ M}\Omega.\text{m}$
Nominal Velocity of Propagation			$66.6 \pm 3\%$
Capacitance			$67 \pm 5 \text{ pF/m}$
Characteristic Impedance at 20°C,200MHz			$75 \pm 5\Omega$
PACKING			WEIGHT
Roll – 280x280x70(mm)	100m/roll		3kg
Wooden drum - 300x300x200(mm)	250m/drum		11.8.kg