REVISED: 2011-07-04 **PRINTED**: 2014-01-29

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME SUNISO 4GS

CHEMICAL NAME Petroleum Hydrocarbon INDUSTRIAL SECRETS

MANUFACTURER JAPAN SUN OIL CO., LTD.

Trusty Kojimachi Bldg., 3-4 Kojimachi Chiyoda-ku,

Tokyo 102-0083 JAPAN Tel: 3-3238-0235

2. COMPOSITION/INFORMATION ON INGREDIENTS

The ingredients in this product are on TSCA Inventory and in CAS.

3. HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***

Not expected to cause a severe emergency hazard.

PRIMARY ENTRY ROUTES: Skin

INHALATION -----

Inhalation of vapor or mist may result in dizziness and nausea.

SKIN -----

Prolonged and/or repeated contact may cause skin irritation and inflammation.

FYF -----

Contact with the eye may cause irritation and redness.

INGESTION -----

Ingestion may result in nausea and/or diarrhea.

Acute toxicity : LD50 > 5g/Kg

CARCINOGENICITY -----

Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

Meets EU requirement of less than 3%(w/w) DMSO extract for total Poly Cyclic Aromatics compounds (PCAs) using IP-346.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ------

Personnel with pre-existing skin disorders should avoid contact with this product.

4	FIF	2ST	AID	ME	ΔSI	IR	F.S
╼.		`U I			~~	J 1 \	$ \circ$

FIUSH with large amounts of water for at least 15 minutes. If redness or irritation persists, contact a physician.

SKIN -----
Wash with soap and water. Wash clothing before reuse. If irritation or rash develops, obtain medical assistance.

INGESTION -----
Do not induce vomiting!

Call a physician.

INHALATION -----

Move to fresh air.

Keep a victim warm by covering with a blanket and in quiet.

Assist breathing if necessary. Contact a physician.

5. FIRE FIGHTING MEASURES

SPECIFIC HAZARD

--- FLAMMABLE LIMITS IN AIR ---

LOWER EXPLOSIVE LIMIT (LEL) ...: N/D % VOL. UPPER EXPLOSIVE LIMIT (UEL) ...: N/D % VOL.

FLASH POINT > 170°C (COC)

AUTOIGNITION TEMP: N/D

--- NFPA CLASSIFICATION --- HAZARD RATING ----- HEALTH - 1 0 - LEAST 3 - HIGH

FIRE - 1 1 - SLIGHT 4 - EXTREME

REACTIVITY - 0 **2- MODERATE**

FIRE AND EXPLOSION HAZARDS -----

Can be made to burn.

EXTINGUISHING MEDIA -----

Halon Dry Chemical, CO₂, Foam, Water Mist or fog.

SPECIAL FIRE FIGHTING INSTRUCTIONS -----

Wear self-contained breathing apparatus. Do not use forced stream as this could cause fire to spread.

6. ACCIDENTAL RELEASE MEASURES

SPILL/LEAK PROCEDURES -----

Stop spill at source if possible without risk. Contain spill. Eliminate sources of ignition. Spill area will be slick. Recover all possible material for reclamation. Use non-flammable absorbent material to pick up remainder of spill.

7. HANDLING AND STORAGE

HANDLING AND STORAGE -----

Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapor.

NFPA Class IIIB storage. Wash thoroughly after handling.

WORK/HYGIENIC PRACTICES -----

Wash hand with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use gasoline, solvent, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse.

Launder or discard contaminated shoes and leather gloves.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS -----

5[mg/m³] mineral oil mist (ACGIH 8 hour TWA).

ENGINEERING CONTROLS -----

Use adequate ventilation to keep oil mists of this material below applicable standard(s). See section on occupational exposure limits.

EYE/FACE PROTECTION -----

Safety glasses or splash goggles. Have suitable eye wash water available.

SKIN PROTECTION -----

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing.

Acceptable materials for gloves are polyvinyl chloride; neoprene; nitrile; polyvinyl alcohol; viton.

RESPIRATORY PROTECTION -----

Normally not required if adequate ventilation. If occupational exposure limits are exceeded wear NIOSH/MSHA approved apparatus.

OTHER/GENERAL PROTECTION -----

If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard.)

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: Wide Range

MELTING POINT N/A: SPECIFIC GRAVITY: 0.91: PACKING DENSITY N/A

VAPOR PRESSURE < 0.03 ([Pa] at 25°C) VAPOR DENSITY > 10 (AIR=1) SOLUBILITY IN WATER: Insoluble PH INFORMATION N/A % VOLATILES BY VOL:

EVAPORATION RATE: Negligible **OCTANOL / WATER COEFF:** N/D

APPEARANCE: Pale Yellow Liquid

Slight Odor ODOR:

ODOR THRESHOLD N/D

Negligible

10. STABILITY AND REACTIVITY	
STABILITY	
Stable	
CONDITIONS TO AVOID (STABILITY)	
Sources of ignition.	
INCOMPATIBLE MATERIALS	
Strong oxidizing agents such as chromic acid, hydrogen peroxide and bromine.	
HAZARDOUS DECOMPOSITION PRODUCTS	
Upon combustion, CO ₂ and CO are generated.	
HAZARDOUS POLYMERIZATION	
Polymerization will not occur.	
11. TOXICOLOGICAL INFORMATION	
11. TOXICOLOGICAL INFORMATION	
ACUTE STUDIES	
Tests on similar materials show a low order of acute oral and dermal toxicity.	
EYE EFFECTS	
Minimal irritation on contact.	
SKIN EFFECTS	
Practically non-toxic if absorbed. May cause mild irritation with prolonged and recontact.	epeated
ACUTE ORAL EFFECTS	
Tests on similar materials indicate low order of acute oral toxicity.	
ACUTE INHALATION EFFECTS	
Low acute toxicity expected on inhalation.	
This product is severely hydrotreated. This product has not been found to be carcinor a potential carcinogen. This product is not listed as carcinogenic or a potential carcinogen by the National Toxicology Program, by the I.A.R.C. monographs or by 0	otential
12. ECOLOGICAL INFORMATION	
AQUATIC RELEASE	
Advise authorities if product has entered or may enter watercourses or sewer drains.	
13. DISPOSAL CONSIDERATIONS	
SPILL, LEAK OR RELEASE	
Stop leak, dike up large spills. Use inert absorbent material such as earth, sand, or vermi clean-up.	culite for

Dispose of in accordance with Local, State, and Federal government regulations.

WASTE DISPOSAL METHOD -----

14. TRANSPORT INFORMATION

Proper Shipping Name : Not regulated by DOT (Contains oil)

Hazard Class : Not Applicable DOT ID No. : Not Applicable

DOT Shipping Label : Not regulated by DOT

Usual Shipping Containers : Rail cars, Tank truck, Drums.

Transport Temperature Deg.C : Ambient to max 60 °C

15. REGULATORY INFORMATION

U.S.FEDERAL REGULATORY INFORMATION -----

SARA 302 Threshold Planning Quantity : N/A SARA 304 Reportable Quantity : N/A

SARA 311 Categories : Immediate (Acute) Health Effects -- No

Delayed (Chronic) Health Effects -- No Fire Hazard -- No Sudden Release of pressure Hazard -- No Reactivity Hazard -- No

Comprehensive Environmental Response, Compensation and liability Act (CERCLA) -------

No chemicals in this product are subject to the reporting requirements of CERCLA.

EUROPEAN (EU) FEDERAL REGULATORY INFORMATION -----

The ingredients in this product are listed on the European Inventory of Existing Commercial Substances.

The base oil has an IP-346 value of <3%.

16. OTHER INFORMATION

DISCLAIMER -----

The information contained herein is based upon data believed to be Reliable and reflects our best professional judgment.

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use.

Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).