COLENT

Floor Paint

Attractive and hard wearing, transforms drab, stained or scuffed concrete and similar surfaces. Suitable for floors

in warehouses, workshops shop floors garages, basements, etc.

Coverage: up to 8m2/ltr (two coats recommended).





HERLOCK Instant Nails

A high strength gap filling solvent-free adhesive that produces a quick 'grab' and replaces mechanical fixings in a multitude of home improvement applications.

Dries white and is over-paintable when dry.





-6500K

310ml

Anti-Slip Floor Paint

Tuffgrip

Solvent free industrial quality floor paint. Applied by roller as a one-coat system, to provide traction in areas of slip hazard. Hard wearing, epoxy resin anti-slip coating

suitable for use on heavy trafficked concrete, stone steel and wooden floor surfaces.

Coverage:



Colour	Order Code SOL-721
Mid Grey	-3050E
Safety Yellow	-3080H
Tile Red	-3100K

Instant Adhesive

High performance cyanoacrylate adhesive suitable for use on metal, plastic, china, leather, wood, glass and rubber. Bonds in seconds.





1001 uses in the **Home and**

Workshop





For Glass & **Plastics Ceramics** Order Code SHK-725 Size

-6010K



3g

Heavy Duty Spray Adhesive

Provides a flexible but ultra strong bond for many applications from foam backed carpets and carpet tiles, underfelt, flexible foams, fabrics, felt and cork to plywood, softwood, MDF, laminates, metal, hardboard, glass and rigid plastics.

Size: 500ml.



Hygienic Floor Paint

Suitable for floors in warehouses, workshops, shop floors, garages, basements, etc. Oil resistant and easy to clean. No primer required.

Hygienic

Water-based anti-bacterial topcoat for floors where hygiene control is essential, including hospitals, kitchens etc. Approved biocide paint with exceptional abrasion resistance. Easy to clean - resistant to oils, solvents

and many chemicals. Coverage: up to 8m² per litre (two coats recommended).

Size: 5 ltr.



Colour	Order Code SOL-721	
Dark Grey	-2010A	

Enamel Paint

This tough enamel has long lasting flexibility when used to cover rust, bare metal and wood, repelling moisture to give long term protection. It must be applied in temperatures of 5° C or above and is sag resistant to eliminate brush strokes, dilutable by white spirit and can be used for interior or exterior applications.



RAL	Colour	Size	Order Code SOL-721	
9005	Black	1ltr 2.5ltr 5ltr	-6110A -6110C -6110E	
5012	Blue	2.5ltr	-6112C	
6010	Green	1ltr 2.5ltr	-6114A -6114C	
3000	Red	1ltr 2.5ltr	-6117A -6117C	
9010	White	1ltr 2.5ltr 5ltr	-6118A -6118C -6118E	
1007	Yellow	1ltr 2.5ltr	-6120A -6120C	