



Non FR Work Apparel/Storage Bags

Coveralls

WK-605-PC (shown)
65% polyester/35% cotton. Pre-shrunk permanent press. Bi-swing back. Concealed 2-way brass zipper front. Seven pocket style with side openings for access to inner clothing. (7¾ oz.)

Specify color: white, charcoal, navy blue, spruce green, chocolate brown, postman blue.

WK-605-C

100% cotton. Pre-shrunk. Plain back concealed brass button front. Seven-pocket style with side openings for access to inner clothing. (8½ oz.)

Specify color: charcoal, chocolate brown, white, natural, navy blue, spruce green, suntan, postman blue, Fisher herringbone stripe (10 oz.).

WK605-PC

1700

1600



Office, Lab and Shop Coat

1600 (30")

Office Coat (shown)

1700 (40")

Lab Coat (shown)

5½ oz. poly-cotton. Three-pocket style. Matching pearl buttons. Specify color: white, light blue, navy blue.

PC-1800 (42")

Shop Coat,
7¾ oz. poly-cotton

Specify color: white, navy blue, postman blue, and white with navy blue trim.

C-1800 (42")

Shop Coat,
8½ oz. 100% cotton

Four-pocket style. Concealed brass button front. Specify color: white, navy blue, postman blue, white with navy blue trim, suntan, spruce green, and 10 oz. Fisher Herringbone.



Duffel Bags

907	General Use	18"W x 9½"H x 9½"D
909-J	Jumbo Style	24"W x 13½"H x 13½"D
909	Fire Fighter's Bag	23"W x 11"H x 13½"D

Available with or without shoulder straps.

All bags are available in your choice of Cordura® nylon, nylon on vinyl or vinyl-coated polyester. See Price List for colors.



Storage and Respirator Bags

900	Half Face Respirator	6¾"W x 8"H x 4½"D
901	Full Face Respirator	9"W x 12"H x 6"D
902	Goggle Cover	6¾"W x 4½"H x 3½"D

Respirator bags come standard with belt loops. Shoulder strap or waist belt available.



One-Panel Screens (with legs)

Available sizes (width x height):

- 5' x 4'
- 6' x 4'
- 6' x 5'
- 6' x 6' (most popular, shown)
- 8' x 5'
- 8' x 6'
- 8' x 8'



Improve the levels of safety and productivity at your facility. Choose a system that will protect you from welding and grinding hazards.

All fabrics available as screen inserts. Most popular fabrics are:

12 oz. olive drab, 13 mil. Weldview in assorted colors, fiberglass (plain or coated), and aluminized fabrics.

Screens are attached to frames with nylon beaded ties. Platform legs available for all screens. Casters available, two casters per platform leg.

Two-Panel Screens (platform legs optional)

Available sizes (width x width x height):

- 4' x 4' x 4'
- 5' x 5' x 5'
- 6' x 6' x 6' (shown)
- 8' x 8' x 6'
- 8' x 8' x 8'



Ready Roll Curtains 14 mil. TRANSPARENT (RR-14)

When ordering please specify material color number.

- Yellow (02)
- Orange (03)
- Grey (04)
- Blue (05)
- Green (06)



Rolls are 25 yards long with grommets on 12" centers. Maximum height 64". Easy attachment to any hook system, cut as needed with any utility knife.

Three-Panel Screens (platform legs optional)

Available sizes (width x width x width x height):

- 2' x 4' x 2' x 4'
- 4' x 4' x 4' x 4'
- 3' x 4' x 3' x 5'
- 3' x 6' x 3' x 5'
- 5' x 5' x 5' x 5'
- 4' x 4' x 4' x 6'
- 6' x 6' x 6' x 6' (shown)
- 8' x 8' x 8' x 8'



Welding Strip Curtains

For high traffic areas, these PVC Strip Curtains use universal pre-studded, zinc-plated hardware that can economically solve your OSHA and regulatory problems.

When ordering, please specify material color number:

- Amber (31)
- Aztec Red (32)
- Charcoal (33)



Four-Panel Screens (with legs)

Available sizes (width x width x width x width x height):

- 6' x 6' x 6' x 6' x 6' (shown)
- 6' x 8' x 6' x 8' x 6'
- 8' x 8' x 8' x 8' x 6'
- 8' x 8' x 8' x 8' x 8'



Weld Strip Doors Replacement Strips and Bulk Rolls

When ordering, please specify material color number.

- Amber (31)
- Aztec Red (32)
- Charcoal (33)

BULK ROLLS		
Size	Stock #	Length
8" x .080"	C8	300
12" x .120"	C12	200
CUT STRIPS (full foot increments — pkg. of 5)		
Size	Stock #	
8" x .080"	C8-1	
12" x .120"	C12-1	

8" x .080" 50% OVERLAP
Door Size
4' x 7'
4' x 8'
5' x 7'
6' x 7'
6' x 8'

12" x .120" 67% OVERLAP
Door Size
8' x 8'
8' x 10'
10' x 10'
10' x 12'
12' x 12'



Welding Blankets

Curtains		Material	Weight	Description	Roll Width
	Olive Drab Duck		OD-12 oz.	General use flame, water and mildew resistant. Treated cotton duck. Most economical. 12 oz. is standard. 10 oz and 14.9 oz. are available.	36"
			OD-10 oz.		48"
			OD-14.9 oz.		60" 72"
	Weldview		WV - 13-14 mil. Yellow, orange, grey, green and blue	Translucent vinyl, filters most U.V. Reduces visible flash and allows light in work areas. CFM approved.	62"
Blankets		Material	Weight	Description	Roll Width
	Heat Cleaned Glass		HCG-18 oz.	Most economical, lightweight, fiberglass. Melting temperature of 1000°F. Good for light welding protection.	40"
					60"
					72"
	Generic Glass Cloth - Heavy		GGCH - 35 oz.	Heavier weight fiberglass. Melting temperature of 1000°F. Good for stress relief and moderate molten splash or sparks.	40"
					48"
					60"
					72"
	Blackflex		BF - 23 oz.	Durable material with proprietary coating on two sides. Fiberglass base. 400°F working temperature, 1000°F melting temperature. Good for sparks and slag. Will take higher heats when used on a vertical plane.	40"
					60"
					72"
	Goldenglass		GLG - 24 oz.	Durable material with proprietary coating on one side. 400°F working temperature, 1000°F melting temperature. Good for sparks and slag.	40"
					60"
					72"
	Silica Cloth		SC-18 - 18 oz.	Protects from sparks, splatter, and molten metal. Up to 1800°F working temperature. Melting temperature near 3000°F. Good for stress relief. Not recommended for areas with high abrasion.	36"
			SC-36 - 36 oz.		
	Silicone-Coated Fiberglass		SCF - 30 oz.	General purpose, sheds oils, sparks and splatter. Working temperature up to 500°F. Melting temperature of 1000°F. Good abrasion resistance.	60"
	Leather Welding Blanket		CL - 3½ oz. per sq. ft.	Abrasion resistant and durable with good flexibility. Protects from moderate sparks and splatter.	—
	Aluminized Kevlar® Blend		AKV - 19 oz.	Reflects up to 2000°F radiant heat. When used in work area, can minimize heat transmission and provide a more comfortable work environment. Will protect from sparks and splatter when used on a vertical plane.	40"