

Heavy-duty power combined with untethered freedom – that's what you get with Snap-on® cordless tools. The perfect solution for low, medium and high torque applications, they're lightweight, comfortable and made with higher-grade materials inside and out for ultimate durability and longevity.

A FULL BATTERY OF BATTERIES.

Our 18 V MonsterLithium batteries provide light weight and long usage, and contain high-grade lithium cells. As well as a built-in fuel gauge and a micro-controller that protects the motor from overheating. Our 14.4 V MicroLithium batteries charge in just 55 minutes, decreasing downtime considerably.

CORDLESS





Cordless Impacts

Specifications	CT8850	CT8810A	CT761A	CT725A
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	18	18	14.4	14.4
Square Drive, inches (mm)	1/2 (13)	3/8 (10)	3/8 (13)	1/4 (6)
Torque Output, ft-lb (N•m)	600 (813)	230 (311.8)	120 (163)	70 (95)
Blows Per Minute, BPM	2280	3480	3,000	3,000
Free Speed, RPM	1900	2400	2,500	2,500
Height w/Battery, inches (mm)	10.2 (259)	9.5 (241)	7.7 (195)	7.7 (195)
Length, inches (mm)	9.6 (244)	6.5 (165)	6.3 (160)	6.3 (160)
Weight w/Battery, lb (kg)	7.3 (3)	4.5 (2.4)	2.5 (1.1)	2 (0.9)
Charge Time (minutes)	60	60	55	55
Warranty (battery)	2 Years	2 Years	1 Year	1 Year
Warranty (tool and charger)	2 Years	2 Years	1 Year	1 Year
Pinned Anvil Version	CT8850P	CT8810AP	—	—
Quick Change Chuck Version (hex size of chuck)	CT8850QC (7/16)	CT8810AQC (1/4)	CT761AQC (1/4)	CT725AQC (1/4)
Tool Only	CT8850DB	CT8810ADB	CT761ADB	CT725ADB

†CE

Drills/Drivers

Specifications	CDR8850H	CDR8815	CDR761B	CDRR761	CTS761A
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	18	18	14.4	14.4	14.4
Chuck Cap., inches (mm)	1/2 (13)	1/2 (13)	3/8 (10)	3/8 (10)	1/4 (6)
Torque Output, in-lb (N•m)	450 (50.9)	500 (57)	150 (16.9)	150 (16.9)	150 (17)
Clutch Settings	22	22	9	9	9
Gear Box Type	2-speed	2-speed	2-speed	2-speed	2-speed
RPM (Low)	0–500	0–520	400	400	0–400
RPM (High)	0–1,800	0–1780	1,400	1,400	1,400
Length, inches (mm)	10 (39.4)	8.8 (22.4)	7.5 (190.5)	13.3 (337.8)	5.8 (147.3)
Weight w/Battery, lb (kg)	5.2 (2.3)	4.75 (22.4)	2.4 (1.1)	3.1 (1.4)	2 (0.9)
Charge Time (minutes)	60	60	55	55	55
Warranty (battery)	2 Years	2 Years	1	1	1
Warranty (tool and charger)	2 Years	2 Years	1	1	1
Tool Only	CDR8850HDB	CDR8815DB	CDR761BDB	CDRR761DB	CTS761ADB

†CE

Reciprocating Saw

Specifications	CTRS8850	CTRS761A
Battery Type	MonsterLithium 4.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	18	14.4
Stroke Length, inches (mm)	1 (25.4)	0.50 (12.7)
Strokes Per Minute	2,400	3,100
Length, inches (mm)	18 (457)	12 (304)
Height w/Battery, inches (mm)	8.25 (210)	—
Weight With Battery Pack, lb (kg)	7.7 (3.4)	3.2 (1.5)
Charge Time (minutes)	60	55
Warranty (battery)	2 Years	1 Year
Warranty (tool and charger)	2 Years	1 Year
Tool Only	CTRS8850DB	CTRS761ADB

Adhesive Gun

Specifications	CAG8850DBKIT
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Weight w/Battery, lb (kg)	2.7 (1.2)
Actuation	Manual Feed
Adhesive Output	2.2 lb Per Hour
Adhesive Stick	1/2" Round
Nozzle Type	Ball Check
Stroke: Grams Per Squeeze	1.2
Service Rating	Industrial
Temperature	350 °F Nominal, 380 °F Maximum
Temperature Control	Solid State
Warranty	2 Years



• Read and follow safety messages for each type of Cordless Tool on the following pages and the safety precautions on pages W1 to W4

CORDLESS: QUICK REFERENCE CHART

Polishing/Prep Tools

Specifications	CTPP761A
Battery Type	MicroLithium 2.0 Ah
Battery Voltage	14.4
Spindle Thread, inches	5/16"-24 UNF
Disc Pad, inches (mm)	3 (76)
Free Speed, RPM, Low (High)	0-3,500 (0-15,000)
Charge Time (minutes)	60
Weight w/Battery, lb (kg)	1.8 (0.8)
Length, inches (mm)	5.2 (132)
Height, inches (mm)	7.8 (198.1)
Width, inches (mm)	1.9 (48.5)
Warranty (Battery)	1 year
Warranty (Tool and Charger)	1 year
Tool Only	CTPP761ADB

18 V Grease Guns

Specifications	CGG8850
Operating Power, V	18
Low Output Pressure, PSI (bar)	7500 (517)
High Output Pressure, PSI (bar)	3000 (206)
Grease Reservoir Capacity, oz (g)	14.5 (411)
Hose Length, inches (mm)	30 (762)
Operating Temperature, °F (°C)	0-122 (-18-50)
Operating Current, A	4
Rated Current, A	5
Lubricant (Grease)	Up to NLGI #2
Grease Output Low, oz/min (g/min)	3.8 (108)
Weight w/Battery, lb (kg)	8.0 (3.6)

Specifications	CGG8850
Sound Pressure Level, dBA	72.5
Uncertainty K, dBA	3
Sound Power Level, dBA	83.5
Uncertainty K, dBA	3
Vibration Level, m/s ²	1.4
Warranty Tool, years	1
Warranty Tool, years	2
Battery	CTB8185 (1)
Charger	CTC720
Tote Bag	CTUTOTEABK
Tool Only	CGG8850DB

Grinders/Cut-off Tools

Specifications	CTGR8850	CTGR8855
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah
Battery Voltage	18	18
Wheels, inches	4-1/2 or 5	4-1/2 or 5
Arbor Size, inches (mm)	7/8 (22)	7/8 (22)
Free Speed, RPM	8,000	8,000
Charge Time (minutes)	60	60
Switch Type	Slide Switch	Safety Switch
Length w/battery, inches (mm)	16.5 (419)	16.5 (419)
Weight w/Battery, lb (kg)	5.7 (2.4)	5.5 (2.5)
Warranty (battery)	2 Years	2 Years
Warranty (tool and charger)	2 Years	2 Years
Tool Only	CTGR8850DB	CTGR8855DB

14.4 V Microlithium Cordless Ratchets

Specifications	CTR761C	CTR714A
Battery Type	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	14.4	14.4
Square Drive, inches (mm)	3/8 (10)	1/4 (8)
Torque Output, ft-lb (N•m)	40 (54)	35 (47)
Free Speed, RPM	275	350
Charge Time (minutes)	55	55
Weight w/Battery, lb (kg)	2.5 (1.1)	2 (.91)
Height w/Battery, inches (mm)	12.2 (310)	10.75 (273)
Warranty (battery)	1 Year	1 Year
Warranty (tool and charger)	1 Year	1 Year
Tool Only	CTR761CDB	CTR714ADB



Cordless Impacts

CT8850 18 V 1/2" Drive MonsterLithium Impact Wrench Kit

- 600 ft-lb of torque output breaks stubborn fasteners loose easily
- Digital microprocessor-controlled switch, maximizes performance, run time and durability
- Built-in brake stops anvil and prevents tool from throwing fasteners and sockets
- Super bright 1 W LED illuminates work area
- USB Built into charger
- Includes (2) MonsterLithium batteries, charger and tote bag

Specifications	CT8850	CT88500	CT8850HV	CT8850G
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah
Battery Voltage	18	18	18	18
Charge Time (minutes)	60	60	60	60
Square Drive, inches (mm)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)
Anvil Type	Friction Ring	Friction Ring	Friction Ring	Friction Ring
Torque Output, ft-lb (N•m)	600 (813)	600 (813)	600 (813)	600 (813)
Blows Per Minute, BPM	2280	2280	2280	2280
Free Speed, RPM	1900	1900	1900	1900
Length, inches (mm)	9.6 (244)	9.6 (244)	9.6 (244)	9.6 (244)
Weight w/Battery, lb (kg)	7.3 (3)	7.3 (3)	7.3 (3)	7.3 (3)
Warranty (battery)	2 Years/1,000 Cycles	2 Years/1,000 Cycles	2 Years/1,000 Cycles	2 Years/1,000 Cycles
Warranty (tool and charger)	2 Years	2 Years	2 Years	2 Years
Pinned Anvil Version	CT8850P	CT8850P	CT8850P	CT8850P
Quick Change Chuck Version (hex size of chuck)	CT8850QC (7/16)	CT8850QC (7/16)	CT8850QC (7/16)	CT8850QC (7/16)
Tool Only	CT8850DB	CT8850DB	CT8850DB	CT8850DB
Battery (qty)	CTB8185 (2)	CTB8185 (2)	CTB8185 (2)	CTB8185 (2)
Tote Bag	CTUTOTEABK	CTUTOTEABK	CTUTOTEABK	CTUTOTEABK
Battery Charger	CTC720	CTC720	CTC720	CTC720
Optional Protective Boot	CT8850BOOT	CT8850BOOT	CT8850BOOT	CT8850BOOT

CE



- Use only impact sockets and accessories with impact wrenches
- Read safety precautions on pages W1 to W4

CORDLESS: 18-VOLT IMPACT WRENCHES



CT8810A



CT8810AG



CT8810AO



CT8810AHV

CT8810A Series 18 Volt Impact Wrenches (3/8")

18 V 3/8" Drive MonsterLithium Impact Wrench Kit

- Provides an incredibly powerful 230 ft-lb of torque at a lightweight 4.25 lb
- High-capacity 72 watt-hour, 18 V MonsterLithium battery for long run time
- The CT8810A can remove 544 bolts tightened at 200 ft-lb on one battery charge
- Cold-formed, alloy steel anvil for maximum durability
- The digital fuel gauge and micro-controller in the lithium battery monitors temperature and amperage to prevent motor overheating
- Ergonomics designed into the over-molded grip and cushion-mounted motor provides continuous use without fatigue
- A portable powerhouse that will withstand the toughest conditions whether in or out of the shop
- Kit includes (2) batteries, charger and tote

Color	Red	Green	Orange	Hi-Vis
Specifications	CT8810A†	CT8810AG	CT8810AO	CT8810AHV
Description	18 V 3/8" Drive MonsterLithium Impact Wrench Kit	18 V 3/8" Drive MonsterLithium Impact Wrench Kit	18 V 3/8" Drive MonsterLithium Impact Wrench Kit	18 V 3/8" Drive MonsterLithium Impact Wrench Kit
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah
Battery Voltage	18	18	18	18
Square Drive, inches (mm)	3/8 (10)	3/8 (10)	3/8 (10)	3/8 (10)
Anvil Type	Friction Ring	Friction Ring	Friction Ring	Friction Ring
Torque Output, ft-lb (N•m)	230 (311.8)	230 (311.8)	230 (311.8)	230 (311.8)
Blows Per Minute, BPM	3,480	3,480	3,480	3,480
Free Speed, RPM	2,400	2,400	2,400	2,400
Charge Time (minutes)	60	60	60	60
Length, inches (mm)	6.5 (165)	6.5 (165)	6.5 (165)	6.5 (165)
Weight w/ Battery, lb (kg)	4.5 (2.4)	4.5 (2.4)	4.5 (2.4)	4.5 (2.4)
Warranty (battery)	2 Years/1,000 Cycles	2 Years/1,000 Cycles	2 Years/1,000 Cycles	2 Years/1,000 Cycles
Warranty (tool & charger)	2 Years	2 Years	2 Years	2 Years
Pinned Anvil Version	CT8810AP	—	—	CT8810AP
Quick Change Chuck Version (hex size of chuck)	CT8810AQC (1/4")	—	—	CT8810AQC (1/4")
Tool Only	CT8810ADB	—	—	CT8810ADB
Battery (qty)	CTB8185 (2)	CTB8185 (2)	CTB8185 (2)	CTB8185 (2)
Tote Bag	CTUTOTEABK	CTUTOTEABK	CTUTOTEABK	CTUTOTEABK
Battery Charger	CTC720	CTC720	CTC720	CTC720
Optional Protective Boot	CT8810BBOOT	CT8810GBBOOT	CT8810OBBOOT	CT8810VBBOOT

†CE – DE, ES, GB, FR, IT, NL, UL, CUL

CT8815A Series 18 Volt Impact Wrenches (1/2")

18 V 1/2" Drive MonsterLithium Cordless Impact Wrench

- Provides 230 ft-lb at a light weight of 4.5 lb
- High capacity 72 watt-hour, 18 V MonsterLithium battery for long run time
- The CT8815A can remove 525 bolts tightened at 200 ft-lb on one battery charge
- Cold-formed, alloy steel anvil for maximum durability
- The digital fuel gauge and micro-controller in the lithium battery monitors temperature and amperage to prevent motor overheating
- Ergonomic overmolded cushion grip for continuous use with less fatigue
- Includes impact wrench, (2) batteries, (1) charger and a tote bag



CT8815A



CT8815AP

Specifications	CT8815A	CT8815AP
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah
Battery Voltage	18	18
Charge Time (minutes)	60	60
Square Drive, inches (mm)	1/2 (13)	1/2 (13)
Anvil Type	Friction Ring	Pinned
Torque Output, ft-lb (N•m)	230 (311.8)	230 (311.8)
Blows Per Minute, BPM	3,480	3,480
Free Speed, RPM	2,400	2,400
Length, inches (mm)	6.5 (165)	6.5 (165)

Specifications	CT8815A	CT8815AP
Weight With Battery Pack, lb (kg)	4.5 (2.4)	4.5 (2.4)
Warranty (battery)	2 Years/1,000 Cycles	2 Years/1,000 Cycles
Warranty (tool and charger)	2 Years	2 Years
Tool Only	CT8815ADB	CT8815APDB
Battery (qty)	CTB8185 (2)	CTB8185 (2)
Tote Bag	CTUTOTEABK	CTUTOTEABK
Battery Charger	CTC720	CTC720
Optional Protective Boot	CT8810BOOT	CT8810BOOT

†CE – DE, ES, GB, FR, IT, NL, UL, CUL

CORDLESS: 18-VOLT PLATFORMS

Drills/Drivers

CDR8850H 1/2" 18 V MonsterLithium Cordless Hammer Drill Kit

- 1/2" single sleeve steel chuck with carbide jaws
- Heavy-duty gearing designed for metal drilling
- Over-molded ergonomic cushion grip absorbs vibration and reduces user fatigue
- Variable-speed switch maximizes performance and control
- 22-position clutch with two-speed gearbox provides torque control for the correct application
- Super bright 1-watt LED illuminates work area
- Stainless-steel motor screen keeps debris out of motor to extend life
- Temperature protection and shut down protects the tool from excessive heat damage
- LED fault signal provides a visual warning the tool is going to shut down
- Soft start trigger ensures smooth start up of tool
- Includes impact wrench, (2) CTB8185 MonsterLithium battery packs and CTC720 charger in CTUTOTEABK tote bag
- UL and cUL Listed
- CE DE, ES, GB, FR, IT, NL



CDR8850H

Specifications	CDR8850H
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Chuck Cap., inches (mm)	1/2 (13)
Torque Output, ft-lb (N•m)	450 (51)
Clutch Settings	22
Gear Box Type	2-speed
RPM (Low)	0-500
RPM (High)	0-1,800
Charge Time (minutes)	60
Length, inches (mm)	10.25 (260)
Weight w/Battery, lb (kg)	5.2 (2.3)

Specifications	CDR8850H
Height w/Battery, inches (mm)	—
Warranty (tool and charger)	2 Years
Warranty (battery)	2 Years/1,000 Cycles
Battery (qty)	CTB8185 (2)
Tote Bag	CTUTOTEABK
Battery Charger	CTC720
Tool Only	CDR8850HDB
Color Option: Green	CDR8850HGG
Color Option: Orange	CDR8850HHO
Color Option: Hi-Vis	CDR8850HHV



- Use only impact sockets and accessories with impact wrenches
- Read safety precautions on pages W1 to W4

CORDLESS: 18-VOLT PLATFORMS



CDR8815



CDR8815G



CDR8815O



CDR8815HV

CDR8815 Series 18 Volt Drills (1/2" Capacity)**18 V 1/2" MonsterLithium Compact Cordless Drill Kit**

- Heavy-duty gearbox provides higher spindle lock torque – 500 in-lb
- Precision keyless chuck with carbide jaws has external steel sleeve to help withstand abuse
- Heat-treated alloy gears provide strength and durability for longer tool life
- Variable-speed digital switch allows user to accurately control torque
- Glass filled nylon housing is durable and is able to withstand high impact
- Ergonomic over molded cushion grip allows for better tool control with less stress and strain
- 22-position clutch – dial in desired torque for application and get job done quickly
- 1/2" keyless chuck and spindle lock, change bits with one hand
- Oversize cushion trigger and comfort cushion handle
- Side handle for added support
- CE – DE, ES, GB, FR, IT, NL, JP

Specifications	CDR8815
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Charge Time (minutes)	60
Chuck Cap., inches (mm)	1/2 (13)
Torque Output, ft-lb (N•m)	500 (678)
Clutch Settings	22
Gear Box Type	2-speed
Hammer Mode	—
RPM (Low)	0–520
RPM (High)	0–1780
Length, inches (mm)	7.9 (201)

Specifications	CDR8815
Weight w/Battery, lb (kg)	4.5 (2.4)
Height, inches (mm)	9.5 (241)
Warranty (battery)	2 Years
Warranty (tool and charger)	2 Years
Battery (qty)	CTB8185 (2)
Tote Bag	CTUTOTEABK
Battery Charger	CTC720
Tool Only	CDR8815DB
Green	CDR8815G
Orange	CDR8815O
Hi-Vis	CDR8815HV

CTRS8850 Series Reciprocating Saw

CTRS8850 18 V Cordless Reciprocating Saw Kit

- 75 A rated, heavy duty variable-speed trigger provides long life and is contoured to reduce user fatigue
- Heavy duty 14 gauge internal wiring withstands high current loads during heavy sawing
- Spring loaded blade retention system requires no tools and ejects broken blades easily
- Nonslip cushion grip nose reduces vibration and provides positive tool control
- Heavy duty armature and balanced motor design provide smooth operation
- Sealed nose mechanism prevents dirt and sawing debris from damaging internal components
- Includes tool, (1) battery, a charger and a tote bag



CTRS8850

Specifications	CTRS8850†
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Charge Time (minutes)	60
Stroke Length, inches (mm)	1 (25.4)
Strokes Per Minute	2,400
Length, inches (mm)	18 (457)
Weight With Battery Pack, lb (kg)	7.7 (3.4)
Warranty (tool and charger)	2 Years
Warranty (battery), years/cycles	2/1,000
Battery (qty)	CTB8185
Tote Bag	POWERTOTE
Battery Charger	CTC720†
Tool Only	CTRS8850DB

CGG8850 18 V Grease Gun

CGG8850 18 V Cordless Grease Gun Kit

- Two-speed, hi-torque 18 V DC motor delivers outstanding flow and pressure
- 36" high-pressure hose with spring guard and coupler
- Accessible check valve and combination air bleeder/filler valve
- Dual motor protection includes self-resetting thermo-coupler
- Machined and hardened piston with plated steel barrel and premium grease follower
- Ergonomically designed to reduce fatigue and increase productivity
- 18 V high-amperage lithium ion battery provides outstanding run time
- Works well in cold environments
- Kit includes tool, (1) battery, a charger and a tote bag



CGG8850

Specifications	CGG8850
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Charge Time (minutes)	60
Capacity, Tubes Per Charge	up to 27 (Free Flow), up to 17 (@1,000 PSI)
Hose Length, inches (mm)	36 (914)
Weight With Battery Pack, lb (kg)	7.9 (3.6)
Warranty (tool and charger)	2 Years
Warranty (battery), years/cycles	2/1,000
Battery (qty)	CTB8185 (1)
Tote Bag	POWERTOTE
Battery Charger	CTC720
Tool Only	CGG8850DB



• Read safety precautions on pages W1 to W4

CORDLESS: 18-VOLT PLATFORMS



CTGR8850



CTGR8855

CTGR8850/CTGR8855 Grinders/Cut-off Tools**CTGR8850 18 V MonsterLithium Cordless Angle Grinder/Cut-Off Tool**

- 8,000 RPM handles most grinding jobs with ease
- Ultra slim head – lets you get into areas other grinders cannot
- Battery rotates 270° – the battery will not get in the way
- Takes 4-1/2" or 5" wheels - more options to get the job done fast
- Anti-vibration handle – allows you to work longer and more comfortably
- Replaceable motor screen – keeps debris out of the motor so the tool lasts longer
- Seven position safety guard – lets you tackle most jobs with less effort
- Toolless guard removal – simply pull one guard off and slide the other one on
- Includes tool, (1) battery, a charger and a tote bag



CAG8850DBKIT

18 V Cordless Adhesive Gun

- High efficiency melt chamber up to 2.2 lb of material output per hour
- State of the art electronics for consistent performance
- Precision, solid state temperature control
- Kit includes glue gun, (3) different nozzles and (6) assorted adhesive sticks
- Easy Squeeze Two Finger Trigger
- Low Battery/Auto Shut Off Alarm
- Unique design allows for constant use with no fatigue
- Rugged High Impact Nylon Housing
- On/Off Activator
- One push start up for rapid <4 minute warm up time
- Visual indicator allows the user to quickly see the state of operation
- Ready/On/Low Battery Indicator
- Battery and charger sold separately
- UL® and cUL® listed

Specifications	CTGR8850	CTGR8855
Battery Type	MonsterLithium 4.0 Ah	MonsterLithium 4.0 Ah
Battery Voltage	18	18
Charge Time (minutes)	60	60
Wheels, inches	4-1/2 or 5	4-1/2 or 5
Arbor Size, inches (mm)	7/8 (22)	7/8 (22)
Free Speed, RPM	8,000	8,000
Length w/battery, inches (mm)	16.5 (419)	16.5 (419)
Warranty (tool and charger)	2 Years	2 Years
Warranty (battery)	2 Years	2 Years
Tool Only	CTGR8850DB	CTGR8855DB
Battery (qty)	CTB8185 (1)	CTB8185 (1)
Battery Charger	CTC720 (1)	CTC720 (1)
Tote Bag	CTUTOTEABK	CTUTOTEABK
Replacement Grinding Wheel	PT450-WH (4.5")	PT450-WH (4.5")
Replacement Cut-off Wheel	CTGR-CW50	CTGR-CW50
Switch Type	Slide Switch	Safety Switch



CADP8850KIT

CADP8850KIT Paint-less Dent Removal System

- Pulls small and medium size dents
- Saves time without damaging the paint
- No paint or fillers required
- Superior pull strength glue
- High strength pull tabs do not stretch
- Glue gun required to melt glue sticks (not included)

Specifications	CAG8850DBKIT
Battery Type	MonsterLithium 4.0 Ah
Battery Voltage	18
Actuation	Manual Feed
Adhesive Output	2.2 lb Per Hour
Adhesive Stick	1/2" Round
Nozzle Type	Ball Check
Stroke: Grams Per Squeeze	1.2
Service Rating	Industrial
Temperature	350 °F Nominal, 380 °F Maximum
Temperature Control	Solid State
Weight w/Battery, lb (kg)	2.7 (1.2)
Warranty	2 Years



14.4 Volt MicroLithium Impact Wrenches

CT761A 14.4 V 3/8" Drive MicroLithium Cordless Impact Wrench Kit

- 120 ft-lb torque output
- 2,500 RPM free speed
- Digital variable-speed toggle style trigger for precise control
- Tri-beam headlights illuminate work area
- Built-in brake stops the tool from throwing sockets and fasteners
- Over current and thermal protection for the motor
- Under voltage protection will not overdraw the battery
- Built-in gauge lets you know the state of the battery charge
- Screened motor keeps debris from entering critical components
- Over and under temperature protection keeps tool operating at peak efficiency
- Glass-filled nylon housing for durability
- CE-DE, ES, FR, IT, GB, NL, JP

CT725A 14.4 V 1/4" Drive MicroLithium Cordless Impact Wrench Kit

- 70 ft-lb of torque output
- Variable-speed digital toggle-style trigger
- Built-in brake stops the anvil from spinning
- Twin-beam LED lights
- Built-in fuel gauge

Specifications	CT761A†	CT725A†
Battery Type	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	14.4	14.4
Charge Time (minutes)	55	55
Square Drive, inches	3/8 (13)	1/4 (6)
Torque Output, ft-lb (N•m)	120 (163)	70 (95)
Free Speed, RPM	2,500	2,500
Blows Per Minute, BPM	3,000	3,000
Length, inches (mm)	6.3 (160)	6.3 (160)
Height w/Battery, inches (mm)	7.7 (195)	7.7 (195)
Weight w/Battery, lb (kg)	2.5 (1.1)	2 (0.9)
Warranty (Tool and Charger), years	1	1
Warranty (Battery), years	1	1
Quick Change Chuck Version (hex size of chuck, inches)	CT761AQC (1/4)	CT725AQC (1/4)
Tool Only	CT761ADB	CT725ADB
Battery (Quantity)	CTB8172BK (2)	CTB8172BK (2)
Tote Bag	CTUTOTEABK	CTUTOTEABK
Charger	CTC772A	CTC772A
Green	CT761AG	CT725AG
Orange	CT761AO	CT725AO
Hi-Vis	CT761AHV	CT725AHV

*UL® and CUL listed

†CE



- Do not use grinders or cut-off tools without the guard
- Read safety precautions on pages W1 to W4

CORDLESS: 14.4-VOLT MICROLITHIUM™ PLATFORMS



CTS761A

Specifications	CTS761A†
Battery Type	MicroLithium 2.0 Ah
Battery Voltage	14.4
Charge Time (minutes)	55
Square Drive, inches (mm)	1/4 (6) Hex
Torque Output, in-lb (N•m)	150 (17)
Clutch Settings	9
Free Speed, RPM	400/1,400
Length, inches (mm)	5.8 (147.3)
Height, inches (mm)	7.8 (198.1)
Weight w/Battery, lb (kg)	2 (0.9)
Warranty (Tool and Charger), years	1
Warranty (Battery), years	1

CTS761 Series 14.4 Volt MicroLithium Screwdriver

CTS761A 14.4 V 1/4" Hex MicroLithium Cordless Screwdriver Kit

- 150 in-lb of torque output
- Two-speed gearbox – 400/1,400 RPM
- 300 in-lb manual spindle lock
- Nine-position clutch allows you to dial in the proper torque
- Glass-filled nylon housing for durability
- Digital variable-speed toggle-style trigger for precise control
- Twin-beam headlights illuminate the work area
- Built-in brake stops the tool from throwing sockets and fasteners
- Overcurrent protection protects the electronics; under voltage protection will not overdraw the battery
- Built-in gauge displays the battery charge state
- Screened motor keeps debris from entering critical components

Specifications	CTS761A†
Tool Only	CTS761ADB
Battery (Quantity)	CTB8172BK (2)
Tote Bag	CTUTOTEABK
Charger	CTC772A
Green	CTS761AG
Orange	CTS761AO
Hi-Vis	CTS761AHV

*UL® and CUL listed

†CE



CTRS761A

Specifications	CTRS761A
Battery Type	MicroLithium 2.0 Ah
Battery Voltage	14.4
Charge Time (minutes)	55
Length, inches (mm)	12 (304)
Weight with Battery Pack (Lithium Ion), lb (kg)	3.2 (1.5)
Variable Speed Switch	Yes
Stroke Length, inches (mm)	0.50 (12.7)
Strokes Per Minute	3,100

14.4 V MicroLithium Saw

CTRS761A 14.4 V MicroLithium Cordless Reciprocating Saw Kit

- 3,100 strokes per minute
- Variable speed switch
- Dual chuck mechanism (Quick Chuck)
- Depth guide that can be adjusted without use of tools
- Small and lightweight making it great for working in confined areas
- Integrated LED work light
- Battery gauge LED
- Fuel gauge to indicate the battery's state of charge
- Footplate can be adjusted to six different positions
- Quick one-handed blade release
- Housing screen keeps debris out of motor
- Lock-off switch located above the trigger
- Variable speed controlled trigger switch

Specifications	CTRS761A
Warranty (tool and charger)	1 Year
Warranty (battery)	1 Year
Battery (Quantity)	CTB8172BK (2)
Battery Charger	CTC772A
Tool Only	CTRS761ADB
Tote Bag	CTUTOTEABK
Green	CTRS761AG
Hi-Vis	CTRS761AHV
Orange	CTRS761AO



14.4 V Microlithium Cordless Ratchets

- Digital variable-speed trigger for precise control
- Built-in brake stops the tool from throwing sockets and fasteners; Uses a chromed wear bushing to increase brake life
- Over and under temperature protection keeps tool operating at peak efficiency
- Cushion-grip handle provides positive tool control with less fatigue
- Large, accessible reversing knob for easy mechanism direction changes
- Battery "Fuel Gauge" LED cleverly integrated into handle
- Utilizes a 14.4 V MicroLithium 2.0Ah battery pack
- MicroLithium battery recharges in 55 minutes
- Integrated LED headlight

Specifications	CTR761C	CTR714A
Battery Type	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	14.4	14.4
Charge Time (minutes)	55	55
Square Drive, inches (mm)	3/8 (10)	1/4 (8)
Torque Output, ft-lb (N•m)	40 (54)	35 (47)
Manual Torque, ft-lb (N•m)	158 (214)	46 (62)
Free Speed, RPM	275	350
Height w/Battery, inches (mm)	12.2 (310)	10.75 (273)
Weight w/Battery, lb (kg)	2-1/2	2 (.91)
Warranty (tool and charger)	1 Year	1 Year
Warranty (battery)	1 year	1 Year
Tool Only	CTR761CDB	CTR714ADB
Battery (qty)	CTB8172BK (2)	CTB8172BK (2)
Tote Bag	CTUTOTEABK	CTUTOTEABK
Battery Charger	CTC772A	CTC772A
Green	CTR761CG	CTR714AG
Hi-Vis	CTR761CHV	CTR714AHV
Orange	CTR761CO	CTR714AO

CE – DE, ES, FR, IT, GB, NL, JP



- Do not use in an explosive or flammable atmosphere
- Read safety precautions on pages W1 to W4

CORDLESS: 14.4-VOLT MICROLITHIUM™ PLATFORMS



CDR761B



CDRR761

Specifications	CDR761B	CDRR761
Battery Type	MicroLithium 2.0 Ah	MicroLithium 2.0 Ah
Battery Voltage	14.4	14.4
Charge Time (minutes)	55	55
Chuck Cap., inches (mm)	3/8 (10)	3/8 (10)
Clutch Settings	9	9
Torque Output, in-lb (N•m)	150 (16.9)	150 (16.9)
Free Speed, RPM, Low (High)	0-400 (0-1,400)	0-400 (0-1,400)
Height, inches (mm)	7.8 (198.1)	7.8" (198.1 mm)
Length, inches (mm)	7.5 (190.5)	7.5" (190.5 mm)
Weight w/Battery, lb (kg)	2.4 (1.1)	2.4 lbs. (1.1 kg)
Operating Temperature, °F (°C)	-4-120 (-20-60)	-4-120 (-20-60)

CDR761 Series 14.4 Volt Drills (3/8" capacity)

CDR761B 14.4 V 3/8" MicroLithium Cordless Drill Kit

- 150 in-lb of torque handles a wide variety of applications
- Two-speed drill (400/1,400 RPM) low speed for higher torque applications/high speed for steel drilling
- Variable speed switch – good featherability at low speed for driving screws and control
- Nine-position clutch delivers 8-50 in-lb torque
- Lightweight drill with battery only 2.4 lb
- 3/8" keyless drill chuck – single sleeve durable steel chuck makes changing bits easy
- Cushion grip handle – nonslip, comfort for the operator, positive tool control allows the operator to work longer with less fatigue
- Small size to get in tight spots: under dash, firewall, etc.
- One-year full warranty and serviced by Snap-on® Service Centers
- Built-in gauge displays the battery charge state
- Includes tool, two batteries, charger and tote bag

Specifications	CDR761B	CDRR761
Sound Pressure Level, dB(A)	73.7	73.7
Sound Power Level, dB(A)	85.3	85.3
Warranty (Tool and Charger)	1 Year	1 Year
Warranty (Battery)	1 Year	1 Year
Tote Bag	CTUTOTEABK	CTUTOTEABK
Tool Only	CDR761BDB	CDRR761DB
Battery (Quantity)	CTB8172BK (2)	CTB8172BK (2)
Battery Charger	CTC772A	CTC772A
Green	CDR761BG	CDRR761G
Hi-Vis	CDR761BHV	CDRR761HV
Orange	CDR761BO	CDRR761O



CTPP761A

Specifications	CTPP761A
Battery Type	14.4V MicroLithium
Charge Time (minutes)	60
Free Speed, RPM, Low (High)	0-3,500 (0-15,000)
Height, inches (mm)	7.8 (198.1)
Length, inches (mm)	5.2 (132)
Weight w/Battery, lb (kg)	1.8 (0.8)
Operating Temperature, °F (°C)	-4-140 (-20-60)
Sound Pressure Level, dB(A)	72
Sound Power Level, dB(A)	83.6
Battery (Quantity)	CTB8172BK (2)
Battery Charger	CTC772A

14.4 V MicroLithium Polishing/Prep Tool

- Two speed gearbox—3,500/15,000 RPM
- Compact and lightweight
- Variable speed trigger
- Slide bar forward/spindle lock
- 2.0 Ah battery pack
- Battery capacity fuel gauge
- 5/16"-24 UNF spindle thread
- Includes various polishing and sanding pads

Specifications	CTPP761A
Spindle Thread, inches	5/16"-24 UNF
Disc Pad, inches (mm)	3 (76)
Width, inches (mm)	1.9 (48.5)
Storage Temperature, °F (°C)	-4-140 (-20-60)
Warranty (Battery), years	1
Warranty (Tool and Charger), years	1
Green	CTPP761AG
Orange	CTPP761AO
Hi-Vis	CTPP761AHV
Tool Only	CTPP761ADB

Batteries not included



CTLED8850



CTLZ761



CTL761



CTLU761



CTLUH761

Flashlights

CTLED8850 18 V MonsterLithium Cordless LED Work Light

- Super-bright light—500 lumens
- Dual reflector system—beam or flood light
- 120° rotating head
- Dual brightness settings (500 and 250 lumens)
- 8-hour minimum run time (high setting)
- Tempered glass lens
- Resists automotive fluids
- Low battery indicator (10 minutes)
- Battery and charger not included

CTLZ761 14.4 V MicroLithium Work Light

- 200 lumens output
- Low battery indicator (10 minutes)
- Four-hour run time
- Tempered glass lens
- Resists automotive fluids
- Impact modified nylon housing
- Uses CTB8172BK 14.4 V MicroLithium Battery and CTC772A Charger
- Battery and charger not included

CTL761 14.4 V MicroLithium Rechargeable Cordless Work Light

- 200 lumens output
- 120° rotating head
- Eight-hour run time with low battery indicator
- Tempered glass lens
- Battery (CTB8172BK) and charger (CTC772A) not included
- Aluminum head
- Resists automotive fluids
- Impact-modified glass-filled nylon housing
- High quality LED bulb
- Battery and charger not included

CTLU761 14.4 V MicroLithium Cordless 60 LED Utility Light

- 540 lumens, ultra bright light output
- Four-hour run time
- High-impact plastic light tube and housing
- Red LED for ten-minute low battery warning indicator
- Use with 14.4 V MicroLithium rechargeable battery (not included)
- 60 LED bulbs
- Includes hook with pad for hanging
- Works with CTB6172, CTB7172, CTB8172 and CTB8172BK batteries
- Battery and charger not included

CTLUH761 14.4 V MicroLithium Cordless 90 LED Underhood Light

- 800 lumens, ultra bright light output
- Three-hour run time, ideal for underhood, undercarriage and over dash applications
- Expandable 81" clamp to position light at work area
- High impact plastic light tube and housing
- 10-minute low battery indicator
- Includes hook with peg for hanging
- Works with CTB6172, CTB7172, CTB8172 and CTB8172BK batteries
- Battery and charger not included

Stock No.	Description	Color
CTLED8850G	18 V MonsterLithium Cordless LED Work Light	Green/Black
CTLED8850HV	18 V MonsterLithium Cordless LED Work Light	Hi-Vis
CTLED8850O	18 V MonsterLithium Cordless LED Work Light	Orange/Black

Stock No.	Description	Color
CTLU761G	Cordless MicroLithium 60 LED Utility Light	Green
CTLU761HV	14.4 V MicroLithium Cordless 60 LED Utility Light	Hi-Vis
CTLU761O	Cordless MicroLithium 60 LED Utility Light	Orange

Stock No.	Description	Color
CTL761G	14.4 V Rechargeable MicroLithium Cordless Work Light	Green
CTL761HV	14.4 V Rechargeable MicroLithium Cordless Work Light	High Vis
CTL761O	14.4 V Rechargeable MicroLithium Cordless Work Light	Orange

Stock No.	Description	Color
CTLUH761G	14.4 V Cordless MicroLithium 90 LED Underhood Light	Green
CTLUH761HV	14.4 V MicroLithium Cordless 90 LED Underhood Light	Hi-Vis
CTLUH761O	14.4 V Cordless MicroLithium 90 LED Underhood Light	Orange



• Read safety precautions on pages W1 to W4



CTL8850



CTL8850G



CTL8850HV



CTL8850O

Flood Lights

CTL8850 18 V MonsterLithium Cordless LED Floodlight

- 18 V Lithium Cordless LED Floodlight
- Super bright four LED light—750 lumens
- Compact design for versatile use
- Light rotates 120° and swivels 180° to direct light to the work area
- Tempered glass lens
- Dual brightness settings (750 and 375 lumens)
- 8-hour minimum run time (on high setting)
- Resists automotive fluids
- Note: battery and charger are not included

CTL8850G Green LED Floodlight

CTL8850HV Hi-Vis LED Floodlight

CTL8850O Orange LED Floodlight



CTLUV761



CTLAR761

Ultraviolet Flashlights

CTLUV761 14.4 V MicroLithium

Cordless UV Work Light

- 14.4 V MicroLithium Cordless leak detection work light
- Compatible with standard leak detection dyes
- Inspection range of 8' or more
- More than 10 hours of run time
- Tempered glass lens
- Resists automotive fluids
- Low battery indicator (10 minutes)
- Works great with ACTR53625 Universal Dye
- Includes fluorescence-enhancing glasses

CTLAR761 14.4 V MicroLithium

Cordless 500 Lumen Angular Light

- 100–500+ lumen range
- 4-1/2–10+ hours runtime
- Hook and magnetic attachment points
- 180° pivot angle

CTLAR761G Green

CTLAR761O Orange

CTLAR761HV High Vis



CTI8850
(battery sold separately)



CTMS8850
(battery sold separately)

Memory Savers/Power Inverters

CTMS8850 18 V Cordless Memory Saver

- Provides temporary power to a vehicle to keep all presets (radio, seats, etc.) intact while the vehicle is being serviced
- Featuring a flexible swiveling head and protective external fuse for maximum flexibility and hassle-free use
- 4-hour run time at 12 V, 1 A; 1-hour run time at 12 V, 4 A (max output)
- 5 V, 1 A USB output
- One-hour run time, 12 V at 4 A
- Protective external fuse

CTI8850 18 V Power Inverter

- 175 W cordless inverter
- 120 V AC power
- 5 V 1 A USB output
- Overload, short circuit and battery voltage protector
- Flexible rotating head
- Protective external fuse and cooling fan
- Provides 110 V AC power anywhere



CTC131



CTC123



CTUSB761



CTUSB8850

Snap-on Battery Chargers

CTC131 14.4 and 18 V Dual Charger

- Charges all 18 V MonsterLithium and 14.4 MicroLithium batteries
- Batteries sold separately

CTC123 14.4-18 V Multi-Bay Charger

- High current charging – 5.8 A
- Simultaneously charges three batteries
- 1 A USB charger
- Low profile
- Fuel gauge indicator
- 500 W output
- Two year warranty
- Charges 18 V MonsterLithium and 14.4 V MicroLithium batteries

USB Power Units

CTUSB761 14.4 V MicroLithium USB Power Unit

- Connect to battery for 5 V, 1 A output, up to two hours
- LED power indicator
- USB protective sliding cover
- Easy on/off switch
- Use with the CTB8172 battery
- Charge cell phones and other small electronic devices
- CE-DE, ES, GB, FR, IT, NL, JP, cULus

CTUSB8850 Four Port USB Device Charger

- Adaptor for 18 V MonsterLithium Ion battery pack
- 4-Port USB charging device
- (4) 5 V Outputs–2 A, 1 A, .5 A, .5 A
- LED indicator for state of charge
- Ratcheting mountable USB head
- Six-hour run time at 5 V/2 A with CTB8185 battery
- Handy on/off switch



• Read safety precautions on pages W1 to W4

CORDLESS: CHARGERS AND BATTERIES



CTB8185



CTB8172BK

Snap-on® Battery Packs

CTB8185 18 V MonsterLithium Slide-on Battery

- 18 V 4.0 Ah high capacity lithium battery
- No self-discharge
- Four LED fuel gauge indicates battery and charger condition
- Operates on current CTC720 and CTC728 chargers
- No memory effect
- Fast 60-minute charge time
- Glass filled nylon housing for durability

CTB8172BK 14.4 MicroLithium Battery

- Small, compact lithium battery with twice the run time of the 7.2 V lithium battery
- 2.0 Ah and weighs only 12 oz; fits 14.4 V 761 series and most 7.2 V 661 series tools
- Fast, 55-minute charge time
- 14.4 V 2.0 Ah high capacity MicroLithium Battery (29 Wh)
- No memory effect, no self discharge
- Glass filled nylon housing for durability

Stock No.	Type	Voltage	Style	Charge Time (minutes)	Use with
CTB8185	Lithium Ion	18	Slide-on	—	Generic to all MonsterLithium 18 V product
CTB8172BK	Lithium Ion	14.4	Tower	55	Generic to all MicroLithium 14.4 V product



CTBA418



CTC123



CTC720



CTC728



CTC772A



CTC131

Snap-on Battery Chargers

CTBA418 Slide-on Battery Adapter

- Adapts the CTB4185 slide-on battery to a post style battery for use in older models of Snap-on® cordless power tools

Stock No.	Type	Applications
CTC123	14.4 / 18 V Multi-Bay Lithium Charger	CTB7172, CTB8172, CTB7185 and CTB8185
CTC420	Multivolt Ni-Cad Charger	Charges all 9.6 V, 14.4 V and 18 V Ni-Cad slide-on or tower style batteries
CTC578	7.2 V DC Mobile Charger	CTB5172 and CTB5196
CTC596	9.6 V Ni-Cad Charger	CTB5172 and CTB5196
CTC620	Dual Chemistry Charger	CTB4145, CTB4147, CTB4185, CTB4187, CTB6185 and CTB6187
CTC720	18 V Lithium Charger	CT7850, CDR7850H, CTL7850, CT7850, CTB7185 and CTB8185
CTC728	12 V DC Lithium Mobile Charger	CT7850, CDR7850H, CTL7850, CT7850, CTB7185 and CTB8185
CTC772A	3.0 A 7.2 V/14.4 V Lithium Charger	Generic to all MicroLithium 14.4 V product
CTC131	14.4 V / 18 V Dual Bay Lithium Charger	CTB7172, CTB8172, CTB7185 and CTB8185

Batteries not included



CTEXTSET



CTS561BITSET



CTS561HOLSTR



CTS561CHUCK

CTS561 Series Screwdriver Accessories

CTEXTSET 4 pc Quick Change Extensions Set

- Includes: CTEXT6 and CTEXT12 quick change extensions plus a T15 TORX® bit (1/4" shank) and a Phillips® bit (power groove hex shank)
- Ideal companion to the CTS series screwdrivers where extended reach is needed

CTS561BITSET 23 pc 1/4" Drive Quick Change Bit Set (Blue-Point®)

- For Snap-on® cordless screwdrivers plus other power drivers
- Quick change hex saves time changing bits
- Manufactured from industrial grade tool steel
- Includes (22) bits (all 3" long) plus a 1/4" square drive (2" long) and storage case

Bits included in CTS561BITSET: PHILLIPS® Bits: #0, #1, #2; Flat Tip Bits: 5/32", 3/16", 7/16", 1/4", 9/32"; TORX® Bits: T10, T15, T20, T25, T27, T30, T40; Hex Bits: 3/32", 7/64, 1/8", 5/32", 3/16", 7/32", 1/4"

CTS561HOLSTR Holster Bit Set

- Includes 3 flat tip bits (3/16", 7/32", 1/4"), 3 Phillips® bits (#0, #1, #2) and 2 TORX® bits (T15, T25)
- Attaches to belt to keep bits close for ready use

CTS561CHUCK 1/4" Quick Change Keyless Drill Chuck

- 1/4" hex shank for fast change over
- Compact size improves access and visibility of drilling surface
- 1/4" chuck capacity provides convenience for small jobs
- 1/32-1/4" drill capacity
- Use for light duty, small holes in metal and wood

CTEXT12 12" Quick Change Extension

- For rotary power tools
- Ideal companion to the CTS561 and CTS561CL series screwdrivers where extended reach is needed
- Accepts all worldwide industrial standards for hex shanks
- Hardened extension directly transfers rotary power without loss of torque
- Hex design eliminates slippage and optimizes power
- Hex lock mechanism better than magnet styles and holds the accessories unit until released
- Maximum RPM: 2,500
- Torque rate: 167 in-lb

CTEXT6 6" Quick Change Extension

- For rotary power tools
- Ideal companion to the CTS561 and CTS561CL series screwdrivers where extended reach is needed
- Accepts all worldwide industrial standards for hex shanks
- Hardened extension directly transfers rotary power without loss of torque
- Hex design eliminates slippage and optimizes power
- Hex lock mechanism better than magnet styles and holds the accessories unit until released
- Maximum RPM: 2,500
- Torque rate: 167 in-lb

ELECTRIC: POLISHER/ENGRAVER



ETB1580B

Polisher

ETB1580B 7" Variable-Speed Polisher (Blue-Point®)

- Six-position speed setting allows user to dial in desired speed
- Soft-start trigger for increased control
- Push button spindle lock for quick and easy pad changes
- Polish and detail autos, trucks and boats



GA236C

Engravers

GA236C Engraver (Blue-Point®)

- Marks all materials
- Includes 3 mm tungsten carbide tip
- Nine-position stroke adjustment to control engraving depth
- Soft coated housing provides better comfort and handling
- 9 position stroke adjustment to control engraving depth
- Super smooth action ideal for precision engraving

GA236C1 Tungsten Carbide Tip

- 3 mm tungsten carbide tip



- Use only impact sockets and accessories with impact wrenches
- Read safety precautions on pages W1 to W4

CORDLESS: INTERNATIONAL PRODUCTS



Europe (Lithium Products)

CTCEU772A 14.4 Lithium Battery Charger (Europe/United Kingdom)

- Charges CTB6172, CTB7172, CTB8172 and CTB8712BK lithium batteries

CTCE720 18V Lithium Battery Charger (Europe)

- Charges all 18 V Lithium slide-on style batteries, including CTB7185 and CTB8185

International Products

Stock No.	Description	Australia	Europe	Japan
CDR8815	18 V Compact Drill	CDRA8815	CDREU8815	CDRJ8815
CDR8850H	18 V Hammer Drill	CDRA8850H	CDREU8850H	CDRJ8850H
CT8810A	18 V 3/8" Impact Wrench	CTA8810A	CTEU8810B	CTJ8810A
CT8815A	18 V 1/2" Impact Wrench	CTA8815A	CTEU8815B	CTJ8815A
CT8810AQC	18 V Impact Wrench - Quick Change Chuck 1/4"	CTA8810AQC	CTEU8810BQC	CTJ8810AQC
CT8850	18 V 1/2" Impact Wrench	CTA8850	CTEU8850A	CTJ8850
CT8850QC	18 V Impact Wrench - Quick Change Chuck 7/16"	CTA8850QC	CTEU8850AQC	CTJ8850QC
CGG8850	18 V Grease Gun	CGGA8850	CGGEU8850	CGGJ8850
CTRS8850	18 V Reciprocating Saw	CTRSA8850	CTRSEU8850	CTRSJ8850
CTGR8850	18 V Grinder / Cut-off Tool	CTGRA8850	CTGREU8850	CTGRJ8850
CT761A	14.4 V 3/8" Impact Wrench	CTA761A	CTU761A	CTJ761A
CT761AQC	14.4 V Impact Wrench - Quick Change Chuck 1/4"	CTA761AQC	CTU761AQC	CTJ761AQC
CT725A	14.4 V 1/4" Impact Wrench	CTA725A	CTU725A	CTJ725A
CTR761C	14.4 V 3/8" Ratchet	CTRA761C	CTRU761C	CTRJ761C
CTR714A	14.4 V 1/4" Ratchet	CTRA714A	CTRU714A	CTRJ714A
CDR761B	14.4 V Drill	CDRA761B	CDRU761B	CDRJ761B
CDRR761	14.4 V Right Angle Drill	CDRA761	CDRREU761	CDRRJ761
CTS761A	14.4 V Screwdriver	CTSA761A	CTSU761A	CTSJ761A
CTS725B	14.4 V Screwdriver	CTSA725B	CTSU725B	CTSJ725B
CTRS761A	14.4 Reciprocating Saw	CTRSA761A	CTRSU761A	CTRSJ761A
CTPP761A	14.4 V Polish Prep Tool	CTPPA761A	CTPPU761A	CTPPJ761A
CTC772A	14.4 V Charger	CTCA772A	CTCEU772A	CTCJ772A
CTC720	18 V Charger	CTCA720	CTCEU720	CTCJ720