

DON'T BUY AN INFERIOR PRODUCT



AIR COMPRESSOR RATING IN ACCORDANCE WITH AUSTRALIAN STANDARD AS 4637-2006





Direct Drive

Electric

PORTABLE AND STATIONAR

• Belt Drive

Petrol

DIRECT DRIVE AIR COMPRESSORS

SP11-10X

2HP AIR COMPRESSOR TRADE DUTY **PORTABLE - UPRIGHT**

SPECIFICATIONS

- Direct Drive
- 150psi

- 126L/min FAD
- 10lt Tank
- 240Volts/10amp
- Filter/Regulator

FEATURES

- · Lightweight & compact Ideal for high rise applications - one man lift • Full brass non-return valve

- Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- · After cooler on direct drive models
- · Soft start valve
- Copper wound motor
- · Cast iron cylinder
- Thermal reset switch

350(L) x 323(w) x 610(h)mm



10 LITRE TANK

REVERSIBLE HANDLE WITH HEIGHT **ADJUST**

LIGHTWEIGHT

COMPACT

29Kg

SP11-12X

2HP AIR COMPRESSOR TRADE DUTY **PORTABLE - UTE PACK**

SPECIFICATIONS

- Direct Drive
- 126L/min FAD
- 150psi
- 10lt Tank
- 240Volts/10amp Filter/Regulator

FEATURES

- · Built tough & compact Ideal for mobile applications - Fits under Tonneau style ute lids
- Full brass non-return valve
- Copper delivery pipe
- 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- Large oil level sight glass
- After cooler on direct drive models
- Soft start valve
- Copper wound motor
- Cast iron cylinder
- Thermal reset switch

865(L) x 400(w) x 518(h)mm



COMPACT

LOW PROFILE

BUILT TOUGH

31Kg

SP11-40X

2HP AIR COMPRESSOR TRADE QUALITY PORTABLE TRADITIONAL

SPECIFICATIONS

- Direct Drive
- 126L/min FAD
- 150psi
- 36lt Tank
- 240Volts/10amp Filter/Regulator

FEATURES

- Lightweight & high trade quality
- One man lift
 Larger tank capacity
- Full brass non-return valve

- Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- Large oil level sight glass
- After cooler on direct drive models
- Soft start valve
- Copper wound motor
- · Cast iron cylinder
- Thermal reset switch

630(L) x 360(w) x 680(h)mm



DIRECT DRIVE AIR COMPRESSORS CONTINUED

SP12-50X

2.5HP AIR COMPRESSOR TRADE OUALITY **PORTABLE**

SPECIFICATIONS

- Direct Drive
- 182L/min FAD
- 150psi
- 50lt Tank
- · 240Volts/10amp
- Regulator

FEATURES

- The ultimate builders companion
- Able to run all nail guns
- · One man lift
- Full brass non-return valve

- Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- · Large oil level sight glass
- · After cooler on direct drive models
- Soft start valve
- Copper wound motor
- Cast iron cylinder Thermal reset switch
- 800(L) x 360(w) x 710(h)mm



BELT DRIVE AIR COMPRESSORS

SP13-50X

2.2HP AIR COMPRESSOR **CAST IRON V-TWIN PORTABLE**

SPECIFICATIONS

- Belt Drive
- 194L/min FAD
- 150psi
- 50lt Tank
- 240Volts/10amp • Filter/Regulator

FEATURES

- Ideal for the builders gang
- Will run several air tools at once
- Full brass non-return valve
- Copper delivery pipe
 Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
 Certified safety valve

- · Large oil level sight glass
- Soft start valve
 Copper wound motor
- Cast iron cylinders
- Thermal reset switch

800(L) x 400(w) x 700(h)mm



SP14

2.5HP AIR COMPRESSOR **CAST IRON V-TWIN PORTABLE**

SPECIFICATIONS

- Belt Drive
- 260L/min FAD
- 150psi
- 60lt Tank
- · 240Volts/10amp
- Filter/Regulator

FEATURES

- Ideal for commercial applications
- Full brass non-return valve
- Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
 Certified safety valve

- · Large oil level sight glass
- Soft start valveCopper wound motor
- Cast iron cylinders
- · Resettable overload protection

950(L) x 370(w) x 780(h)mm





COMPRESSORS



BELT DRIVE AIR COMPRESSORS CONTINUED

SP17

3HP AIR COMPRESSOR CAST IRON V-TWIN PORTABLE - 15AMP

SPECIFICATIONS

- Belt Drive
- 318L/min FAD
- 150psi
- 60lt Tank
- 240Volts/10amp
- Filter/Regulator

FEATURES

- Ideal for commercial applications
- Full brass non-return valve
- · Copper delivery pipe
- 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- · Large oil level sight glass
- · Soft start valve
- Copper wound motor
- Cast iron cylinders
- · Resettable overload protection

950(L) x 370(w) x 780(h)mm



SP17P

6.5HP AIR COMPRESSOR **CAST IRON V-TWIN** PETROL DRIVEN

SPECIFICATIONS

- Belt Drive
- 356L/min FAD
- 150psi
- 60lt Tank
- Filter/Regulator

FEATURES

- · Take anywhere & will run several air tools at once
- · Ideal for commercial applications 6.5hp Torini OHV 4 Stroke Engine
- V-Twin Pump with alloy heads Full brass non-return valve

- Full brass non-return valve
 Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
 Certified safety valve
- Large oil level sight glass
- Soft start valve

1005(L) x 490(w) x 790(h)mm



SP18

3HP AIR COMPRESSOR CAST IRON TRIPLE PORTABLE - 15AMP

SPECIFICATIONS

- · Belt Drive
- 385L/min FAD
- 150psi
- 60lt Tank 240Volts/15amp
- · Filter/Regulator

FEATURES

- · Ideal for commercial applications
- Full brass non-return valve
- Copper delivery pipe
 200mm (8") solid rubber wheels · One-touch (Nitto style) connector
- Certified safety valve
- · Large oil level sight glass
- · Soft start valve
- Copper wound motor
 Cast iron cylinders
- · Resettable overload protection

1020(L) x 440(w) x 890(h)mm





BELT DRIVE AIR COMPRESSORS CONTINUED



3HP AIR COMPRESSOR CAST IRON TRIPLE PORTABLE - 15AMP

SPECIFICATIONS

- Belt Drive
- 385L/min FAD
- 150psi
- 100lt Tank
- 240Volts/15amp
- Filter/Regulator

FEATURES

- Ideal for commercial applications
- Full brass non-return valve
- Copper delivery pipe
 200mm (8") solid rubber wheels
 One-touch (Nitto style) connector
- Certified safety valve
- Large oil level sight glass
- · Soft start valve
- Copper wound motor
- Cast iron cylinders
- · Resettable overload protection



DETACHABLE

100 LITRE TANK

BELT DRIVE AIR COMPRESSORS - STATIONARY

SP25

5.5HP AIR COMPRESSOR **CAST IRON V-TWIN STATIONARY** 3 PHASE

SPECIFICATIONS

- Belt Drive
- 508L/min FAD
- 150psi 200lt Tank
- 3 Phase (415V/50Hz) 10amp per PH

FEATURES

- · Ideal for commercial applications
- · High efficiency induction motor

- Full brass non-return valve
 Copper delivery pipe
 Independent 3 phase switch box operates by a single phase pressure switch
 • One-touch (Nitto style) connector
- Certified safety valve
- · Large oil level sight glass
- · Copper wound motor
- Cast iron cylinders
- Resettable overload protection
- · Filter/regulator



1150(L) x 450(w) x 900(h)mm



COMPRESSORS



BELT DRIVE AIR COMPRESSORS - STATIONARY CONTINUED

254Kg SP35 7.5HP AIR COMPRESSOR **CAST IRON TRIPLE** COMMERCIAL **STATIONARY** GRADE **3 PHASE 3 PHASE SPECIFICATIONS** 15Amp Per Phase Belt Drive • 880L/min FAD • 150psi • 270lt Tank • 3 Phase (415V/50Hz) 15amp per PH **FEATURES** Ideal for commercial applications · High efficiency induction motor • Full brass non-return valve Copper delivery pipe
 Independent 3 phase switch box operates by a single phase pressure switch • One-touch (Nitto style) connector Certified safety valve
 Large oil level sight glass Soft start valve Copper wound motor

1630(L) x 630(w) x 1360(h)mm

SP50

10HP AIR COMPRESSOR CAST IRON TRIPLE STATIONARY 3 PHASE

SPECIFICATIONS

Cast iron cylinders

· Resettable overload protection

- Belt Drive
- 1360L/min FAD
- 150psi
- 270lt Tank
- 3 Phase (415V/50Hz) 18amp per PH

FEATURES

- · Ideal for commercial applications
- · High efficiency induction motor
- Full brass non-return valve
- Copper delivery pipe
 Independent 3 phase switch box operates by a single phase pressure switch
- One-touch (Nitto style) connector
 Certified safety valve
- · Large oil level sight glass
- Soft start valve
- · Copper wound motor
- Cast iron cylinders
- Resettable overload protection





2.2Hp

2.5Hp

3.0Hp

COMPRESSOR PUMPS

COMPRESSOR PUMPS CAST IRON V-TWIN - BELT DRIVE

HORSE POWER SUITS MODEL

SP13-50X 260SP SP14 & SP17 350SP

SPECIFICATIONS

- 150psi 240Volts/10amp Nominal FAD: 194~318L/min



COMPRESSOR PUMPS CAST IRON TRIPLE - BELT DRIVE

SP18 & SP1800

HORSE POWER SUITS

MODEL 460SP

SPECIFICATIONS

- 150psi 240Volts/15amp
 - Nominal FAD: 385L/min



COMPRESSOR PUMPS CAST IRON - BELT DRIVE 3 PHASE

HORSE POWER	FAD	AMP P/PH	SUITS
5.5Hp	508/min	10Amp	SP25
7.5Hp	880/min	15Amp	SP35
10Hp	1360/min	18Amp	SP50

MODEL **SPECIFICATIONS**

485SP

710SP

1085SP

• 150psi • 3 Phase (415V/50Hz)

