



### NON-SPARKING HEX KEYS

#### Copper Beryllium

Product Code	Size (MM)	Overall Length (Inches)	Width (Inches)
NSB320-2	2	2 3/8	1
NSB320-3	3	2 3/8	1
NSB320-4	4	2 1/2	1 3/16
NSB320-5	5	3 1/8	1 1/4
NSB320-6	6	3 3/8	1 7/16
NSB320-7	7	3 1/2	1 11/16
NSB320-8	8	3 5/8	1 3/4
NSB320-9	9	3 7/8	1 3/4
NSB320-10	10	4 3/8	1 3/4

#### Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- Anti-magnetic and highly corrosion resistant.



NSB320-5



### NON-SPARKING ERGO® SLOTTED SCREWDRIVERS

#### Copper Beryllium

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
NSB300-3-50	6 3/4	2	1/8
NSB300-3-75	7 3/4	3	1/8
NSB300-4-75	7 3/4	3	5/32
NSB300-4.5-100	8 3/4	4	3/16
NSB300-4.5-50	6 3/4	2	3/16
NSB300-5-75	7 3/4	3	3/16
NSB300-5-100	8 3/4	4	3/16
NSB300-6-100	8 3/4	4	1/4
NSB300-6-125	9 3/4	5	1/4
NSB300-6-150	10 3/4	6	1/4
NSB300-7-150	10 3/4	6	1/4
NSB300-8-150	10 3/4	6	5/16
NSB300-8-200	12 1/2	7 3/4	5/16
NSB300-9-250	14 1/2	9 3/4	5/16
NSB300-10-200	12 1/2	7 3/4	3/8
NSB300-10-300	12 1/2	7 3/4	3/8
NSB300-11-250	14 1/2	9 3/4	1/2
NSB300-11-300	16 1/2	11 3/4	1/2
NSB300-11-350	18 1/2	13 3/4	1/2
NSB300-12-400	20 1/2	15 3/4	1/2
NSB300-13-450	22 1/2	17 3/4	1/2

#### Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.



NSB300-6-100



NSB301-4-100



## NON-SPARKING ERGO® ELECTRICIAN'S SCREWDRIVERS

### Copper Beryllium

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
NSB301-3-50	6 3/4	2	1/8
NSB301-4-100	8 3/4	4	3/16
NSB301-4-150	10 3/4	6	3/16
NSB301-5-100	8 3/4	4	3/16
NSB301-5-200	12 1/2	7 3/4	3/16
NSB301-6-100	8 3/4	4	1/4
NSB301-8-150	10 3/4	6	3/16
NSB301-10-200	12 1/2	7 3/4	3/8
NSB301-10-300	16 1/2	11 3/4	3/8

### Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.



NSB302-3-150



## NON-SPARKING ERGO® PHILLIPS® SCREWDRIVERS

### Copper Beryllium

Product Code	Overall Length	Blade Length	Point Size
NSB302-0-50	6 3/4	2	0
NSB302-1-100	8 3/4	4	1
NSB302-2-125	9 3/4	5	2
NSB302-3-150	10 3/4	6	3
NSB302-4-300	16 1/2	11 3/4	4

### Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.



NSB304-2-125



## NON-SPARKING ERGO® POZIDRIV® SCREWDRIVERS

### Copper Beryllium

Product Code	Overall Length	Blade Length	Point Size
NSB304-0-50	6 3/4	2	PZ0
NSB304-1-100	8 3/4	4	PZ1
NSB304-2-125	9 3/4	5	PZ2
NSB304-3-150	10 3/4	6	PZ3
NSB304-4-300	16 1/2	11 3/4	PZ4

### Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.