

# FINISHING



## The Best Way To A Great Finish

Today's manufacturing techniques are constantly changing and improving. This has increased the demands for sanders, polishers and buffers, making them a key segment of the process. Improvements in the industry now result in less waste on castings and molded parts, which shifts the emphasis from material removal to surface finishing. Sioux Tools offers a complete line of state-of-the-art orbital sanders, polishers and buffers that will produce the quality finish you require on your final product.

Sioux sanders are engineered to cover the full range of applications in metal, composite, and wood finishing. Our innovative, lightweight designs ensure they perform to the highest standards while still being comfortable to operate. Each delivers unsurpassed power and performance, resulting in the perfect finish.

### FIT TO YOUR APPLICATION

Different applications require different finishing tools. That's why Sioux Tools offers a variety of sanders and polishers with a wide range of configurations.

The RO2512 Series Random Orbital Sanders come with an orbit diameter of either 3/8" (10 mm), 3/16" (5 mm) or 3/32" (3 mm) and a choice of non-vacuum, self-contained Venturi vacuum or remote vacuum ready.

### VARIETY TO CHOOSE FROM

We also offer pistol grip, right angle, vertical, and straight sanders and polishers. Many of these come with your choice of throttle controls that allow the operator to work the way that's most comfortable.



### FINISHING SAFETY

Flying particles can cause eye injury. Proper eye protection must be worn at all times by tools user and bystanders.

A grinding wheel that bursts can cause injury or death. Never mount a grinding wheel or a cutoff wheel on a sander or polisher.

Breathing grinding dust can cause injury. Do not breathe grinding dust. Use approved mask.

Sanders and polishers that do not come to a complete stop before setting aside can cause injury. Be sure the tool has come to a complete stop before setting it aside.

Explosions and fires can cause injury. Only sand metal if the area is free of combustible or explosive materials or vapors.

Contact with sanding disks can cause injury. Wear protective clothing and gloves to protect hands. Keep hands and other body parts away from sanding pads and disks to prevent cutting or pinching.

Sanding or polishing pads, disks or accessories that burst can cause injury. Make sure disks or accessories have a higher speed rating than the tool. Do not exceed rated air pressure.

Prolonged exposure to vibration or an excessive exposed portion of the edge of a disk can cause injury. When using self adhesive sanding disks, make sure to mount them concentrically on the pad.

Tools starting unexpectedly can cause injury. Always remove tool from air supply and activate trigger to bleed air line before making any adjustments, changing accessories, or doing any maintenance or service on tool.

Tools that perform unpredictably can cause injury. Use only sanding and polishing pads, disks and accessories provided or specified by Sioux Tools.



RO2512-50SNP



RO2512-50SRP



RO2512-50FVP

POWER TOOLS

FINISHING: SANDERS

**PERFORMANCE:**

Power: 0.25 hp (0.19 kW)  
Speed: 12,000 rpm

**FEATURES:**

3/32" (3 mm), 3/16" (5 mm) & 3/8" (10 mm) Orbit Diameters  
Built-in Speed Control  
Ergonomic 24-Position Indexable Grip  
Non-Vacuum, Venturi Vacuum & Remote Vacuum

**RO2512 SERIES RANDOM ORBITAL SANDERS**



Model Number	Free Speed	Pad Size	Orbit Diameter	Weight	Height	Air Consumption	Sound Level
PSA Pad	H & L Pad	rpm	in mm	in mm	lb kg	in mm	cfm l/s
<b>0.25 hp (0.19 kW) – 5/16"-24 Spindle Thread – Non-Vacuum</b>							
RO2512-30FNP	RO2512-30FNH	12,000	3 75	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-30SNP	RO2512-30SNH	12,000	3 75	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-35FNP	RO2512-35FNH	12,000	3.5 90	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-35SNP	RO2512-35SNH	12,000	3.5 90	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50FNP	RO2512-50FNH	12,000	5 125	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-50SNP	RO2512-50SNH	12,000	5 125	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50CNP	RO2512-50CNH	12,000	5 125	3/8 10	1.5 0.7	3.3 83	13 6
RO2512-60FNP	RO2512-60FNH	12,000	6 150	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-60SNP	RO2512-60SNH	12,000	6 150	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-60CNP	RO2512-60CNH	12,000	6 150	3/8 10	1.5 0.7	3.3 83	13 6
<b>0.25 hp (0.19 kW) – 5/16"-24 Spindle Thread – Remote Vacuum Ready</b>							
RO2512-30FRP	RO2512-30FRH	12,000	3 75	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-30SRP	RO2512-30SRH	12,000	3 75	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-35FRP	RO2512-35FRH	12,000	3.5 90	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-35SRP	RO2512-35SRH	12,000	3.5 90	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50FRP	RO2512-50FRH	12,000	5 125	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-50SRP	RO2512-50SRH	12,000	5 125	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50CRP	RO2512-50CRH	12,000	5 125	3/8 10	1.5 0.7	3.3 83	13 6
RO2512-60FRP	RO2512-60FRH	12,000	6 150	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-60SRP	RO2512-60SRH	12,000	6 150	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-60CRP	RO2512-60CRH	12,000	6 150	3/8 10	1.5 0.7	3.3 83	13 6
<b>0.25 hp (0.19 kW) – 5/16"-24 Spindle Thread – Self-contained Venturi Vacuum</b>							
RO2512-30FVP	RO2512-30FVH	12,000	3 75	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-30SVP	RO2512-30SVH	12,000	3 75	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-35FVP	RO2512-35FVH	12,000	3.5 90	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-35SVP	RO2512-35SVH	12,000	3.5 90	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50FVP	RO2512-50FVH	12,000	5 125	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-50SVP	RO2512-50SVH	12,000	5 125	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-50CVP	RO2512-50CVH	12,000	5 125	3/8 10	1.5 0.7	3.3 83	13 6
RO2512-60FVP	RO2512-60FVH	12,000	6 150	3/32 3	1.5 0.7	3.3 83	13 6
RO2512-60SVP	RO2512-60SVH	12,000	6 150	3/16 5	1.5 0.7	3.3 83	13 6
RO2512-60CVP	RO2512-60CVH	12,000	6 150	3/8 10	1.5 0.7	3.3 83	13 6

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Comfort Grip • Backing Pad & Wrench

**Accessories:** Sander Accessories, see pages 706-708



Safety Precaution: Read and follow all safety and operation instructions.  
Warning: Face & eye protection must be worn while operating power tools, per ANSI B186.1.





RO2510-44FNC

### PERFORMANCE:

Power: 0.25 hp (0.19 kW)  
Speed: 10,000 rpm

### FEATURES:

Built-in Speed Control  
Ergonomic 24-Position Indexable Grip

## ORBITAL JITTERBUG SANDERS



Model Number	Paper Size		Orbit Diameter		Weight		Height		Air Consumption Free Speed		Sound Level
	in	mm	in	mm	lb	kg	in	mm	cfm	l/s	dB(A)
<b>0.25 hp (0.19 kW)</b>											
RO2510-44FNC	3 3/4 x 4 1/4	95 x 105	3/32	3	1.8	0.8	3.5	90	13	6	81

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual

**Accessories:** Sander Accessories, see pages 706-708

POWER TOOLS

FINISHING: SANDERS



GO459-60SNP



GO459-80SRP

### PERFORMANCE:

Power: 0.45 hp (0.34 kW)  
Speed: 900 rpm

### FEATURES:

3/16" (5 mm) Orbit Diameter  
Built-in Speed Control  
Lever Throttle  
Vacuum & Remote Vacuum  
Ergonomic 24-Position Indexable Grip

## GEARED ORBITAL SANDERS



PSA Pad	Model Number	Free Speed rpm	Pad Size		Weight		Height		Air Consumption		Sound Level
	H & L Pad		in	mm	lb	kg	in	mm	cfm	l/s	dB(A)
<b>0.45 hp (0.34 kW) Non-Vacuum</b>											
	GO459-60SNP	900	6	150	4.4	2	5	127	15	7	82
	GO459-80SNP	900	8	200	4.4	2	5	127	15	7	82
<b>0.45 hp (0.34 kW) Remote Vacuum</b>											
	GO459-60SRP	900	6	150	4.4	2	5	127	15	7	82
	GO459-80SRP	900	8	200	4.4	2	5	127	15	7	82

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual

**Accessories:** Sander Accessories, see pages 706-708



**PERFORMANCE:**

Power: 0.40 hp (0.30 kW)  
Speed: 10,000 rpm

**FEATURES:**

3/16" (5 mm) Orbit Diameter  
Built-in Speed Control  
Aluminum Housing  
Palm & Lever Throttle



658

**600 SERIES RANDOM ORBITAL SANDERS**

Model Number		Free Speed	Pad Size		Orbit Diameter		Weight		Height		Air Consumption		Sound Level
PSA Pad	H & L Pad	rpm	in	mm	in	mm	lb	kg	in	mm	cfm	l/s	dB(A)
<b>0.40 hp (0.30 kW) – Palm Throttle</b>													
PS690 <sup>1</sup>		10,000	5	125	3/16	5	2.9	1.3	4.2	107	20	9	85
697 <sup>1</sup>		10,000	6	150	3/16	5	2.9	1.3	4.2	107	20	9	85
<b>0.40 hp (0.30 kW) – Dual Action – Lever Throttle</b>													
658 <sup>1</sup>		10,000	5	125	3/16	5	3.2	1.5	4.2	107	20	9	85

<sup>1</sup>For remote vacuum ready add suffix V

<sup>1</sup>Not CE Certified **General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Backing Pad & Wrench

**Accessories:** Sander Accessories, see pages 706-708

POWER TOOLS

FINISHING: SANDERS



SPS10P18



SDG10P18

**PERFORMANCE:**

Power: 1 hp (0.75 kW)  
Speed: 6000 rpm – 21,000 rpm

**FEATURES:**

Trigger Start  
Down-Handle Exhaust  
Comfort Grip



**PISTOL GRIP SANDERS**

Model Number	Free Speed	Weight		Height		Air Consumption		Sound Level
	rpm	lb	kg	in	mm	Free Speed	cfm	
<b>1 hp (0.75 kW) – 5" (125 mm) Diameter Backing Pad</b>								
SPS10P6	6000	1.7	0.8	4.5	115	35	17	80
SPS10P18	18,000	1.7	0.8	4.5	115	35	17	80
<b>1 hp (0.75 kW) – 1/4" Collet</b>								
SDG10P18	18,000	1.7	0.8	5.8	145	35	17	86.2
SDG10P21	21,000	1.7	0.8	5.8	145	35	17	86.3

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Comfort Grip

**Accessories:** Sander Accessories, see pages 706-708





SAS03S122-20



SAS05S232-20



SAS10A182-20



77016 Threaded Arbor



300 Series Collet

POWER TOOLS

FINISHING: SANDERS

### PERFORMANCE:

Power: 0.33 hp (0.25 kW) – 1 hp (0.75 kW)  
 Speed: 12,000 rpm – 23,000 rpm

### FEATURES:

Lockoff Lever Throttle  
 Front, Rear, and Vacuum Exhaust  
 Comfort Grip

### RIGHT ANGLE DISC SANDERS



Model Number	Free Speed		Weight		Length		Air Consumption		Sound Level	Spindle Thread
	rpm		lb	kg	in	mm	cfm	l/s		
<b>0.3 hp (0.22 kW) – Lever Throttle</b>										
SAS03S122-20	12,000		1.1	0.5	5.625	143	11	5.2	82.2	1/4"-20
SAS03S202-20	20,000		1.1	0.5	5.625	143	11	5.2	82.9	1/4"-20
<b>0.5 hp (0.37 kW) – Lever Throttle</b>										
SAS05S232-20	23,000		1.3	0.59	5.625	143	23	10.3	88.6	1/4"-20
<b>1 hp (0.75 kW) – Lever Throttle</b>										
SAS10A122-20	12,000		2.15	0.98	7.5	190	30	14	84.6	1/4"-20
SAS10A152-20	15,000		2.15	0.98	7.5	190	30	14	TBD	1/4"-20
SAS10A182-20	18,000		2.15	0.98	7.5	190	30	14	83.4	1/4"-20
SAS10A324	3200		TBD	TBD	TBD	TBD	35	17	TBD	3/8"-24

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Support Handle (1 hp Models) • Spindle Wrenches, 300 Series Collet, 1/4"-20 Threaded Arbor

**Accessories:** Sander Accessories, see pages 706-708





SAS10S125



SAS10A125



SAS10AX125



1287L

**PERFORMANCE:**

Power: 1 hp (0.75 kW)  
Speed: 6000 rpm – 12,000 rpm

**FEATURES:**

Governed & Non-Governed  
Lockoff Lever Throttle  
Rear Exhaust on SAS Series

**RIGHT ANGLE SANDERS**



Model Number	Free Speed		Pad Diameter		Weight		Length		Air Consumption Under Load		Air Consumption Free Speed		Sound Level dB(A)	Spindle Thread
	rpm		in	mm	lb	kg	in	mm	cfm	l/s	cfm	l/s		
<b>1 hp (0.75 kW) – Lockoff Lever Throttle – Rear Exhaust</b>														
SAS10S125	12,000		5	125	3.5	1.6	8.3	210	N/A	N/A	35	17	77	5/8"-11
SAS10A125	12,000		5	125	2.2	1	7.75	134	N/A	N/A	35	17	84.1	5/8"-11
SAS10AX125	12,000		5	125	3.2	1.45	11.25	285	N/A	N/A	35	17	83.2	5/8"-11
<b>1 hp (0.75 kW) – Governed Speed Control – Lockoff Lever Throttle</b>														
1287L <sup>1</sup>	6000		7	175	5.9	2.7	11.3	287	35	17	18	8	85	5/8"-11

<sup>1</sup>Not CE certified.

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Support Handle • Spindle Wrenches • Backing Pad & Nut

Accessories: Sander Accessories, see pages 706-708



1290



1290L



VS20AL-727

**PERFORMANCE:**

Power: 1 hp (0.75 kW) – 2 hp (1.5 kW)  
Speed: 6000 rpm – 7200 rpm

**FEATURES:**

Governed & Non-Governed  
Lever & Thumb Throttle  
Side Exhaust  
Overspeed Shutoff Protection (V Series)

**VERTICAL SANDERS**



Model Number	Free Speed		Pad Diameter		Weight		Length		Air Consumption Under Load		Air Consumption Free Speed		Sound Level dB(A)	Spindle Thread
	rpm		in	mm	lb	kg	in	mm	cfm	l/s	cfm	l/s		
<b>1 hp (0.75 kW) – Thumb Throttle</b>														
1290	5000		7	175	4.1	1.9	7.2	183	30	14	38	18	80	5/8"-11
<b>1 hp (0.75 kW) – Lever Throttle</b>														
1290L	6000		7	175	4.1	1.9	7.2	183	30	14	38	18	80	5/8"-11
<b>2 hp (1.5 kW) Class Vertical Sanders – Governed Speed Control – Lockoff Lever Throttle</b>														
VS20AL-609	6000		9	230	7.4	3.3	5.5	145	75	35	26	12	85	5/8"-11
VS20AL-727	7200		7	175	7.4	3.3	5.5	145	75	35	26	12	85	5/8"-11

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Spindle Wrenches • Backing Pad & Nut

Accessories: Sander Accessories, see pages 706-708





### PERFORMANCE:

Power: 1 hp (0.75 kW)  
Speed: 3000 rpm

### FEATURES:

Governed Speed Control  
Lockoff Lever Throttle  
Spindle Lock  
Remote Exhaust

## RIGHT ANGLE POLISHERS



Model Number	Free Speed		Pad Diameter		Weight <sup>1</sup>		Length		Air Consumption Under Load		Air Consumption Free Speed		Sound Level	Spindle Thread
	rpm		in	mm	lb	kg	in	mm	cfm	l/s	cfm	l/s	dB(A)	
<b>1 hp (0.75 kW) - Lockoff Lever Throttle</b>														
1238L	3000		8	200	7.9	3.6	11.3	287	33	16	16	8	75	5/8"-11

<sup>1</sup> Weight includes pad & holder.

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Remote Exhaust • Support Handle • Backing Pad & Nut • Wool Polishing Pad

**Accessories:** Polisher Accessories, see pages 706-708

### PERFORMANCE:

Power: 1 hp (0.75 kW)  
Speed: 2000 rpm – 3000 rpm

### FEATURES:

Lever & Thumb Throttle  
Side Exhaust  
Comfort Grips



## VERTICAL POLISHERS



Model Number	Free Speed		Pad Diameter		Weight <sup>1</sup>		Length		Air Consumption Under Load		Air Consumption Free Speed		Sound Level	Spindle Thread
	rpm		in	mm	lb	kg	in	mm	cfm	l/s	cfm	l/s	dB(A)	
<b>1 hp (0.75 kW) - Thumb Throttle</b>														
1296	2000		8	200	4.1	1.9	7.1	180	30	14	38	18	80	5/8"-11
1292	3000		8	200	4.1	1.9	7.1	180	30	14	38	18	80	5/8"-11
<b>1 hp (0.75 kW) - Lever Throttle</b>														
1292L	3000		8	200	4.1	1.9	7.1	180	30	14	38	18	80	5/8"-11

<sup>1</sup> Weight includes pad & holder.

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Spindle Wrenches • Backing Pad & Nut • Polishing Pad

**Accessories:** Polisher Accessories, see pages 706-708



### COMFORT GRIPS



Part Number	Description	For Use On
66667	Cushion Grip	690 series

### FIBRE BACKING DISCS

**Part No 586**  
 For use on SPS10P series sanders  
 Packaged in cartons of 6  
 Qty 3 - 3" (75 mm)  
 Qty 3 - 4-1/2" (110 mm)



### SUPPORT HANDLE

**Part No 2362**  
 For use on 2L series straight sanders



### BACKING PADS

For use on SPS10P series sanders



Part Number	Thread	Diameter	
		in	mm
2344*	(5/8)-24	5	125
2364*	(5/8)-11	5	125

\* Includes disc nut 563

### SPEED-LOK BACKING PADS

For use on 1DA series sanders



Part Number	Diameter		Hex Size
	in	mm	
587M	2	50	1/4"
588M	3	75	1/4"

### 7" (175 MM) OR 9" (230 MM) SANDING KITS

For use on 1287, 1287L, 1290, 1290L & VS20 Series



Part Number	Description
<b>545 Standard Kit</b>	
544	Disc holder
548	Backing disc
542	Retainer
524	Retaining nut
<b>545H Heavy-Duty Kit</b>	
544	Disc holder
548H	Heavy-duty backing disc
542	Retainer
524	Retaining nut







## ORBITAL SANDER BACKING PADS

Sioux random orbital backing pads are medium density, urethane pads rated for speeds up to 13,000 rpm. The 5" pads are a 3/8" thick with low profile design, while the 6" pads are 5/8" thick with tapered profile for fine feathering in corners or around edges.

5/16" - 24 Spindle Thread



Part Number	Diameter		Backing	Profile	Style
	in	mm			
591	3	75	PSA <sup>1</sup>	Low	Vac/Non-Vac
591J	3	75	H & L <sup>2</sup>	Low	Vac/Non-Vac
592	3.5	90	PSA <sup>1</sup>	Tapered	Vac/Non-Vac
592J	3.5	90	H & L <sup>2</sup>	Tapered	Vac/Non-Vac
593	5	125	PSA <sup>1</sup>	Low	Non-Vac
593V	5	125	PSA <sup>1</sup>	Low	Vacuum
593J	5	125	H & L <sup>2</sup>	Low	Non-Vac
593JV	5	125	H & L <sup>1</sup>	Low	Vacuum
593SV	5	125	PSA <sup>1</sup>	Low	Screen Vac
594	6	150	PSA <sup>1</sup>	Tapered	Non-Vac
594V	6	150	PSA <sup>1</sup>	Tapered	Vacuum
594J	6	150	H & L <sup>2</sup>	Tapered	Non-Vac
594JV	6	150	H & L <sup>2</sup>	Tapered	Vacuum
594SV	6	125	PSA <sup>1</sup>	Low	Screen Vac

<sup>1</sup> PSA - Vinyl face for pressure sensitive adhesive sanding discs

<sup>2</sup> H & L - Hook and loop face

## POLISHING ACCESSORIES



Part Number	Grit	Grit
846C*	Backing pad (Includes 524)	
1211B*	Wool polishing pad	
524*	Retaining nut	
847	Hook & loop backing pad	1238, 1238L
1220	Hook & loop polishing pad	1292, 1292L
843	Tie-on wool bonnet (pkg 10)	

\* Standard equipment on polishers

## VACUUM CONVERSION KITS



Part Number	For Use On
665	658, 690, 758, 790



## DUSTLESS WET/DRY VACUUMS

### DUSTLESS WET/DRY VACUUM Sioux Model DVS-5

- Outperforms Traditional Shop Vacs
- Two Layers Of Filtration For A Dust-Free Environment
- Powerful 23,000 RPM, 11.5 Amp Electric Motor
- 16 Gallon Capacity
- Does Not Cough Dust When Vacuum Is Turned On
- Convenient Tool Storage Onboard Vacuum
- Filtration Down To .5 Microns
- Quiet Operation Only 81 dB(A)



### DUSTLESS HEPA VACUUM Sioux Model DVH-3

- HEPA Certified
- Filtration Down To .3 Microns
- 16 Gallon Capacity
- Designed For Extra Fine Dust
- Quiet Operation Only 81 dB(A)
- Great For Hexavalent Chromium Applications



## DUSTLESS VACUUM SHROUDS

### RANDOM ORBITAL SANDER VACUUM SHROUD

#### Sioux Models RO25VS-5 and RO25VS-6

- Fit RO25 Series Random Orbital Sanders
- Available For 5" Or 6" Sanders
- Captures 99% Of Airborne Dust
- Protects Workers From Harmful Airborne Dust
- Flexible And Transparent For Better Visibility
- Includes 6 Ft. Vacuum Hose

Part Number	Description
RO25VS-5	5" Vacuum Shroud
RO25VS-6	6" Vacuum Shroud



### DRILL AND RIVET SHAVER VACUUM SHROUD Sioux Model DRVS150

- Can Be Used With Any Drill Or Rivet Shaver
- Suction Holds The Shroud In Place
- Great For Tight Spaces
- Can Be Used For Drilling Holes Up To 1 3/8" Diameter
- Captures 99% Of Airborne Dust
- Protects Workers From Harmful Airborne Dust
- Transparent For Better Visibility
- Includes 6 Ft. Vacuum Hose

## HOSE CUFF ADAPTER SET

- Adapts 1-1/2" hose to 1-1/4" hose
- Connector for 1-1/2" vacuum hose



MV-49

## PNEUMATIC TOOL REMOTE START ADAPTER

- Lets You Start And Stop Your Pneumatic Tool And Vacuum In Synchronization
- Works With Any Pneumatic Tool
- Wireless Radio Operated
- Quick And Easy To Set Up



DVRS-PA

## ELECTRIC TOOL REMOTE START ADAPTER

- Works With Any Electric Power Tool
- Works With Any Vacuum
- Recognizes Up To 16 Tool/Tool Pods
- Wireless Radio Operated
- Quick And Easy To Set Up
- Reduces Trip Hazard (Fewer Cords)



DVRS-EA

## VACUUM REMOTE START ADAPTER

- Allows the use of multiple tools off the same vacuum
- Can be used with any pneumatic tool or electric power tool



DVRS-VA

## HEPA FILTER

- Certified To Meet OSHA, EPA, & NIOSH Guidelines
- Captures Dust Down To .3 Microns
- Large Circumference For Increased Life
- Large Loose Plates For Increased Air Flow



MV-21

## MICRO PRE-FILTER BAG

- Disposable
- Eliminates The Need To Clean Filters
- Retains Strength When Wet
- Holds More Than 40 lbs of Dust And Debris
- Captures Extra Fine Dust Down To .5 Microns
- Extends The Life Of HEPA Filters
- Large Surface Area For Maximum Airflow



MV-52

## FABRIC FILTER SET

- 2 Stage Inner And Outer Filter
- Machine Washable
- Stays Dry At All Times
- Clean Outer Filter Without Opening the Canister
- No Need To Change Filters When Changing From Wet To Dry Vacuuming
- Large Surface Area For Maximum Flow



MV-51

