

Efficient E480

Approx. 2.7ipm

Max. 99 pages

Approx, 50 pages

19 locations

Full Dot LCD

USB 2.0 Hi-Speed

Access Point Mode

Approx. 5.9kg

PG-47: 400

PG-47: 4535*11

CI-57: 300

CL-57: 90

20 Sheets

NA

Approx. 3sec. / 1min (33.6kbps)

Windows: via Fax Modem (MFP)

Windows 8 / Windows 7 /

Mac OS X v10.7.5 and later

Windows Vista / Windows XP

Wireless LAN IEEE 802.11 b/g/n,

PIXMA Printing Solutions, Easy-PhotoPrint+, AirPrint™

Google Cloud Print™, PIXMA

Approx. 7W (0.9W Standby)

Approx. 435 x 295 x 189mm

Wi-Fi connection to PC

Cloud Link (smartphone / tablet),







Efficient E400

X PIXMA Quality. Promised.



SPECIFICAT	ΓIONS		Efficient E610	Efficient E480	Efficient E560	Efficient E510	Efficient E460	Efficient E400	Quality.
Maximum Printing Reso	olution*1		4800 x 1200 dpi	4800 x 1200 dpi	4800 x 1200 dpi	4800 x 1200 dpi	4800 x 600 dpi	4800 x 600 dpi	
Number of Ink Tanks			2	2	2	2	2	2	
Print Speed*2	Document: Colour / B&W	ESAT / Simplex	Approx. 5.2ipm / 8.9ipm	approx. 4.4ipm / 8.8ipm	approx. 5.7ipm / 9.9ipm	approx. 5.0ipm / 8.6ipm	approx. 4.0ipm / 8.0ipm	approx. 4.0ipm / 8.0ipm	
	Photo (4x6")	PP-201 / Borderless	Approx. 46sec.	Approx. 70sec.	Approx. 44sec.	Approx. 44sec.	NA	NA	
Printing Capability	Borderless Prin	ting*3	Up to A4	Up to A4	Up to A4	Up to A4	NA	NA	
Standard Paper Input (Front Cassette / Tray)	Plain Paper (she	eets)	A4 / A5 / B5 / Letter = 100 Legal = 10 (FastFront)	A4 / A5 / B5 / Letter = 100 Legal = 10	A4 / A5 / B5 / Letter = 100 Legal = 10 (FastFront)	A4 / A5 / B5 / Letter = 100 Legal = 10 (FastFront)	A4 / A5 / B5 / Letter = 60 Legal = 10 (Rear Tray)	A4 / A5 / B5 / Letter = 60 Legal = 10 (Rear Tray)	
Scanner Type / Scannin	ng Method		Flatbed & ADF / CIS (Contact Image Sensor)	Flatbed & ADF / CIS (Contact Image Sensor)	Flatbed / CIS (Contact Image Sensor)	Flatbed / CIS (Contact Image Sensor)	Flatbed / CIS (Contact Image Sensor)	Flatbed / CIS (Contact Image Sensor)	
Optical Resolution*4			1200 x 2400dpi	600 x 1200dpi	1200 x 2400dpi	1200 x 2400dpi	600 x 1200dpi	600 x 1200dpi	
Scanning Speed*5	Reflective	A4 Colour / 300dpi	Approx. 15sec.	Approx. 15sec.	Approx. 14sec.	Approx. 14sec.	Approx. 14sec.	Approx. 14sec.	_ , /
Maximum Document Si	ize		A4 / Letter (216 x 297mm)	A4 / Letter (216 x 297mm)	A4 / Letter (216 x 297mm)	A4 / Letter (216 x 297mm)	A4 / Letter (216 x 297mm)*6	A4 / Letter (216 x 297mm)*6	
Copy Speed*7	Document:	sFCOT / Simplex	Approx. 23sec.	Approx. 28sec.	Approx. 25sec.	Approx. 30sec.	Approx. 31sec.	Approx. 30sec.	
	Colour	sESAT / Simplex	Approx. 4.1ipm	Approx. 3.6ipm	Approx. 2.5ipm	Approx. 2.5ipm	Approx. 1.6ipm	Approx. 1.8ipm	

PIXMA Ink

	NA	NA	NA
. pages	1-9 pages / 20 pages	1-21 pages	1-21 pages
	NA	NA	NA
dows 8 / Windows 7 / dows Vista / Windows XP	Windows 8 / Windows 7 / Windows Vista / Windows XP	Windows 8 / Windows 7 / Windows Vista / Windows XP	Windows 8 / Windows 7 / Windows Vista / Windows XP
OS X v10.6.8 and later	Mac OS X v10.6.8 and later	Mac OS X v10.6.8 and later	Mac OS X v10.6.8 and later
	Approx. 1sec.	NA	NA
	7-segment LED	NA	NA
	NA	NA	NA



Approx. 31sec Approx. 30sec. Approx. 2.5ipm Approx. 2.5ipm Approx. 1.6ipm Approx. 1.8ipm NA 1-21 p NA NA NA NA Windo Windo Mac O NA NA NA Wireless LAN IEEE 802.11 b/g/n, USB 2.0 Hi-Speed Wireless LAN IEEE 802.11 b/g/n, USB 2.0 Hi-Speed USB 2.0 Hi-Speed USB 2.0 Hi-Speed PIXMA Printing Solutions, PIXMA Printing Solutions, Easy-Easy-PhotoPrint, PhotoPrint, Easy-PhotoPrint+, Google Cloud Print Google Cloud Print™, Wireless PictBridge, PIXMA Cloud Link (smartphone / tablet), Access Point Mode Approx. 16W (1.7W Standby) Approx. 12W (0.6W Standby) Approx. 11W (1.6W Standby) Approx. 9W (1.0W Standby) Wi-Fi connection to PC

Specification are subject to change without notice.

Fax Transmission Speed*8 Black / Colour

Fax Transmission / Reception Memory*9

Auto Document Feeder (ADF) Paper Handling

Automatic Group Dialing (Fax)

Multiple Copy

PC Fax

Windows

Macintosh

Quick Start

Interface

Operation Panel

Other Features

Power Consumption

Dimensions (W x D x H)

Photo Paper PP-201, 4x6"

(ISO/IEC 24712 test file)*10 (Pages)

(ISO/IEC 29103 test file)*10 (Pages)

Weiaht

Plain Paper A4

Document

(ADF): Colour

Black / Colour

(Please visit www.canon-asia.com

to confirm OS compatiblity and to download the latest driver updates)

sESAT / Simplex

Approx. 3.4ipm

Max. 99 pages

Approx. 50 pages

19 locations

Approx. 4sec

Full Dot LCD

USB 2.0 Hi-Speed

30 Sheets

Approx. 3sec. / 1min (33.6kbps)

Windows: via Fax Modem (MFP)

Windows 8 / Windows 7 /

Windows Vista / Windows XP

Mac OS X v10.6.8 and later

Approx. 19W (1.1W Standby)

Approx. 458 x 385 x 200mm

Approx. 8.4kg

PG-88: 7630*11

PG-88: 800

CI-98: 400

CL-98: 150

- *1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- *2 Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers
- *4 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- *5 Colour document scan speed is measured with ISO/IEC 29183 Target A. Scan speed indicates the time measured between pressing the scan button of the scanner driver and the on-screen status display turns off. Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.
- *6 Document size max. copy area of 203.2 x 277.3mm (with 16.7mm bottom print margin).
- Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183, ADF copy speed is the average of ESAT in General Performance Test for the default simplex mode, ISO/IEC 24735, excluding time to copy the first set. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm-up time
- *8 Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- *9 Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.
- *10 Declared yield value in accordance with ISO / IEC 24711 (for A4 size) using ISO / IEC 24712 test file: and ISO / IEC 29102 (for 4x6" size) using ISO / IEC 29103 test file. Values obtained by continuous printing.
- *11 Estimated Supplemental Yield.

Note: All printers work in Operating Environment of Temperature: 5 - 35°C; Humidity: 10 - 90 % RH (no dew condensation). All printers work in Storage Environment of Temperature: 0 - 40°C; Humidity: 5 - 95 % RH (no dew condensation).

Canon Office

India: Canon India Pvt. Ltd.

Approx. 449 x 304 x 152mm

Approx. 5.4ka

PG-89: 800

CI-99: 300

CL-99: 114

PG-89: 6540*11

Tel: 91-124-4160 000 Fax: 91-124-4160 011 www.canon.co.in

Malaysia: Canon Marketing (Malaysia)

Sdn Rhd Tel: 603-7844 6000 Fax: 603-7845 0505 www.canon.com.mv

Singapore:

Canon Singapore Pte. Ltd. Tel: 65-6799 8888 Fax: 65-6798 8882 www.canon.com.sq

Co. Ltd. Ho Chi Minh City Office & Showroom Tel: 84-8-382 00466 Fax: 84-8-382 00477

www.canon.com.vn

Vietnam:

Approx. 449 x 304 x 152mm

Canon Marketing (Thailand)

Tel: 66-2-3449 999

Fax: 66-2-3449 922

Canon Marketing Vietnam

www.canon.co.th

Approx. 5.3kg

PG-88: 800

CI-98: 400

CL-98: 150

Thailand:

Co. Ltd.

PG-88: 7630*11

South & Southeast Asia Regional Headquarters:

Canon Singapore Pte. Ltd. 1 HarbourFront Avenue #04-01

Keppel Bay Tower Singapore 098632 Tel: 65-6799 8888 Fax: 65-6799 8882 www.canon-asia.com

Canon Business Partners Maldives:

Bangladesh:

Wi-Fi connection to PC

Approx. 3.5kg

PG-47: 400

CL-57: 300

NA

Approx. 426 x 306 x 145mm

J.A.N Associates Ltd Tel: 880-2-8624 102 880-2-9660 601 880-2-9660 359 Fax: 880-2-8610 410

Brunei: Interhouse Company

Tel: 673-2-653 001 Fax: 673-2-653 003

Cambodia:

i-Qlick (Cambodia) Pte Ltd Tel: 855-23-996 638 Fax: 855-23-996 639

Indonesia: PT Datascrin Canon Call Center Tel: 62-21-2922 6000

www.canon.co.id

Fax: 62-21-6544 811-13

Nepal: International Electronics Concern (P) Ltd Tel: 977-1-4421 991 Fax: 977-1-4421 909

> Pakistan: Shirazi Trading Co. (Pvt.) Ltd Tel: 9221-3241 7659 Fax: 9221-3241 7747

Approx. 426 x 306 x 145mm

Approx. 3.5kg

PG-47: 400

CI-57: 300

SIMDI

Tel: 960-333 4421

Fax: 960-333 4424

Myanmar Golden Rock

Tel: 95-1-654 810 to 17

International Co. Ltd.

Fax: 95-1-654 820

Myanmar:

NA


Sri Lanka: Metropolitan Computers

(Pvt.) Ltd. Tel: 94-11-2437 797 Fax: 94-11-2448 980 PIXMA Ink Efficient Printers – deliver low cost and efficient printing.

E610

E560

E510








www.facebook.com/CanonPIXMA









PIXMA Ink Efficient E610



SO Standard Speed



Сору

Measured by ISO/IEC 24734, 29183, 24735 standards

Print up to 800 pages (black ink cartridge)

30-Sheet Automatic Document Feeder

▶ FastFront: Front access to the printer's paper tray and ink cartridges

▶ Print, Copy, Scan and Fax

PIXMA Ink Efficient E480



ISO Standard Speed

2.7_{ipm} Measured by ISO/IEC 24734, 29183, 24735 standards

▶ Print up to 400 pages (black ink cartridge)

- Access Point Mode
- ▶ PIXMA Printing Solutions
- ▶ PIXMA Cloud Link
- ▶ Apple AirPrint*5
- Print, Copy, Scan and Fax

PIXMA Ink Efficient E560



Auto 2-sided print

▶ PIXMA Printing Solutions

Print up to 800 pages

(black ink cartridge)

- ▶ FastFront: Front access to the printer's paper tray and ink cartridges
- Google Cloud Print

PIXMA Ink Efficient E510



Print up to 800 pages (black ink cartridge)

FastFront: Front access to the printer's paper tray and ink cartridges

Auto Power On: Automatically turns the printer on when it detects a new print job



ISO Standard Speed

Measured by ISO/IEC 24734, 29183 standards



1.6_{ipm}

PIXMA Ink Efficient E460




- ▶ PIXMA Printing Solutions
- ▶ PIXMA Cloud Link
- ▶ Google Cloud Print



Measured by ISO/IEC 24734, 29183 standards

Measured by ISO/IEC 24734, 29183 standards

PIXMA Ink Efficient E400



Easy operation

Measured by ISO/IEC 24734, 29183 standards *5 AirPrint and the AirPrint logo are trademarks of Apple Inc.