



Compact and sleek, the new tank design is integrated into the printer to allow the printer to have the smallest footprint* amongst all brands of ink tank printers that use bottled ink refills. Enjoy spill-free refilling with individual bottles which have unique nozzles that fit only into their respective tanks. Auto-duplex printing** affords users up to 50% savings on paper costs by printing automatically on both sides of paper. Remain connected with the option to print wirelessly over network or directly from your mobile devices using Wi-Fi Direct. Rejoice in exceptional print quality with the use of pigment black ink which produces water and smudge-resistant printouts.



L4150



L4160

- Ultra-High Page Yield
- Print Speed
- Duplex Printing**
- Borderless Printing
- Wi-Fi Direct
- Epson Connect
- 2-Year Warranty



Each printer comes bundled with a starter kit of 1 x 127 ml bottle of black pigment ink and 3 x 70 ml bottles of colour ink.



IT'S IN THE DETAILS.

Superior Savings with Auto-Duplex**

Save up to 50% on paper cost with auto-duplex function which reduces paper consumption.

Seamless Connectivity

Share your printer over Wi-Fi, Wi-Fi Direct, and print on the go via a suite of Epson Connect features.

A4 Size Borderless Printing

Large-size photo printing is made possible with borderless printing up to A4 size.

* Results obtained by comparing published specifications of minimum footprint of all brands of ink tank printers using bottled ink refills against the Epson L4150/4160. Results valid as of July 2017.
**Auto-duplex double-sided printing is only available on L4160.

| MODEL NUMBER | L4150 | L4160 |
|---|--|--|
| Printer Type | Print, Scan, Copy | Print, Scan, Copy |
| Printing | | |
| Printing Technology | On-demand ink jet (piezoelectric) | |
| Nozzle Configuration | 180 nozzles Black, 59 nozzles per colour (Cyan, Magenta, Yellow) | |
| Print Direction | Bi-directional printing, Uni-directional printing | |
| Maximum Resolution | 5760 x 1440 dpi (with Variable-Sized Droplet Technology) | |
| Minimum Ink Droplet Volume | 3 pl | |
| Print Speed ¹ | | |
| Draft Text - Memo, A4 (Black ^{†1} / Colour ^{†2}) | Up to 33 ppm / 15 ppm | |
| ISO 24734, A4 (Black / Colour) | Up to 10.5 ipm / 5.0 ipm | Up to 10.5 ipm / 5.0 ipm, Duplex: 6.0 ipm / 4.0 ipm |
| Photo Default - 10 x 15 cm / 4 x 6" ^{†3} | Approx. 69 sec per photo (Border) / 92 sec per photo (Borderless) | |
| Printer Language | ESC / P-R | |
| Automatic 2-sided printing | No | Yes (up to A4) |
| Copying | | |
| Copy Speed | | |
| ISO 29183, A4, Simplex (Black / Colour) | Up to 7.7 ipm / 3.8 ipm | |
| Copy Quality | Draft / Standard | Draft / Standard / Best Quality |
| Maximum Copies from Standalone | 20 copies | 99 copies |
| Reduction / Enlargement | N/A | 25 - 400%, Auto Fit Function |
| Maximum Copy Resolution | 360 x 360 dpi | 1440 x 720 dpi |
| Maximum Copy Size | A4, Letter | |
| Scanning | | |
| Scanner Type | Flatbed colour image scanner | |
| Sensor Type | CIS | |
| Optical Resolution | 1200 x 2400 dpi | |
| Maximum Scan Area | 216 x 297 mm (8.5 x 11.7 ") | |
| Scanner Bit Depth | | |
| Colour | 48-bit input, 24-bit output | |
| Grayscale | 16-bit input, 8-bit output | |
| Black & White | 16-bit input, 1-bit output | |
| Scan Speed (Flatbed) | | |
| Monochrome 200 dpi | 11 sec | |
| Colour 200 dpi | 28 sec | |
| Card Slot | | |
| Type of Direct Printing | N/A | Memory Device |
| Supported Memory Cards | N/A | SD Memory Card |
| Paper Handling | | |
| Paper Feed Method | Friction feed | |
| Number of Paper Trays | 1 (Paper Cassette) | |
| Paper Hold Capacity | | |
| Input Capacity | 100 sheets, A4 Plain paper (80 g/m ²) 20 sheets, Premium Glossy Photo Paper | |
| Output Capacity | 30 sheets, A4 Plain Paper 20 sheets, Premium Glossy Photo Paper | |
| Paper Size | Legal, 8.5 x 13", Letter, A4, 195 x 270 mm, B5, A5, A6, 100 x 148 mm, B6, 5 x 7", 4 x 6", Envelopes #10, DL, C6 | |
| Maximum Paper Size | 215.9 x 1200 mm (8.5 x 47.24 ") | |
| Print Margin | 0 mm top, left, right, bottom via custom settings in printer driver (except plain paper) ^{†5} | |
| Interface | | |
| USB | USB 2.0 | |
| Network | Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct | |
| Network Protocol | TCP/IPv4, TCP/IPv6, LPD, IPP, PORT9100, WSD | |
| Mobile and Cloud Printing | | |
| Epson Connect | Epson iPrint, Epson Email Print, Remote Print Driver | |
| Other Mobile Solutions | Google Cloud Print, Mopria Print Service | Apple AirPrint, Google Cloud Print, Mopria Print Service |
| Control Panel | | |
| LCD Screen | N/A | 1.4" Colour LCD Panel |
| Printer Software | | |
| Operating System Compatibility | Windows XP / XP Professional x 64 Edition / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later | |
| Electrical Specifications | | |
| Rated Voltage | 220 - 240V | |
| Rated Frequency | 50 - 60 Hz | |
| Power Consumption | | |
| Operating | 12 W | 12 W |
| Standby | 3.9 W | 4.3 W |
| Sleep | 0.7 W | 0.7 W |
| Power off | 0.3 W | 0.3 W |
| Noise Level (PC Printing) | | |
| Premium Glossy Photo Paper Best Photo | 5.2 B(A) / 38 dB(A) | 5.0 B(A) / 37 dB(A) |
| Plain Paper Default ^{†4} | 6.4 B(A) / 51 dB(A) | 6.3 B(A) / 50 dB(A) |
| Consumables | | |
| | Page Yield^{†5} | Order Code |
| Black Ink Bottle | 7,500 | C13T03Y100 |
| Cyan Ink Bottle | 6,000 (Composite Yield) | C13T03Y200 |
| Magenta Ink Bottle | | C13T03Y300 |
| Yellow Ink Bottle | | C13T03Y400 |

Dimensions & Weight


L4150

Weight: 5.0 kg (11.0 lb)



L4160

Weight: 5.5 kg (12.1 lb)



^{†1} Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



#1 Black Text #2 Black Text and graphics #3 Photo 4R (4 x 6 ")

^{†2} When printed on Epson Premium Glossy Photo Paper.

^{†3} Otherwise 3mm top, left, right, bottom.

^{†4} Default mode in accordance with ISO7779.

^{†5} In accordance with ISO 24711/24712. Actual yields will vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. A variable amount of ink remains in the cartridges after the "replace cartridge" signal. Part of the ink from the first cartridges is used for priming the printer. Ink is used for both printing and print head maintenance. All inks are used for both black and colour printing.

© 2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information. Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android is a trademark of Google Inc.

Information correct as at June 2019