



Change the way you print A3+ business documents with the Epson WorkForce WF-7211 and WF-7711 duplex printers. Designed for convenience, these smart printers are equipped with a suite of connectivity features, from USB and Ethernet to Wi-Fi Direct and NFC. With PrecisionCore™ technology, fast printing speed consistently delivers success in every detail.













NFC







WorkForce WF-7711



# IT'S IN THE DETAILS.

With PrecisionCore printhead technology, Epson WorkForce WF-7211/WF-7711 excels with speed and quality.

## **Enhanced Productivity**

Experience enhanced productivity with autoduplex capability and PrecisionCore printhead that delivers printing speeds of up to 18ipm.

## **Superior Quality**

Enjoy laser-like quality prints that are water- and smudge-resistant with Epson's DURABrite™ Ultra ink.

## **Affordable Prints**

Achieve greater cost efficiency with high-yield cartridges that deliver high quality prints at lower running costs.





### **WORKFORCE WF-7211/7711**



Model Number	WF-7211	WF-7711
Printer Type	Print	Print, Scan, Copy, Fax with ADF
Printing		
Printing Technology	PrecisionCore Printhead	
Nozzle Configuration	400 x 2 nozzles Black, 128 x 2 nozzle Bi-directional printing, Uni-directiona	es per colour (Cyan, Magenta, Yellow)
Print Direction Maximum Resolution	4800 x 2400 dpi (with Variable-Sized	Droplet Technology)
Minimum Ink Droplet Volume	3.8pl	Dropiet recrinology)
Print Speed <sup>1</sup>		
Draft Text - Memo, A4 (Black*1 / Colour*2	) Up to 32ppm / 20ppm	
ISO 24734, A4 (Black / Colour)	Simplex: Up to 18ipm / 10ipm, Duple	x: 8.7ipm / 6.0ipm
ISO 24734.2, A3 (Black / Colour) Photo Default - 10x15 cm / 4x6" "2#3	Up to 32ppm / 20ppm Simplex: Up to 18ipm / 10ipm, Duplex: 8.7ipm / 6.0ipm Simplex: Up to 10ipm / 5.0ipm, Duplex: 6.0ipm / 3.7ipm Approx. 42 sec per photo (Border), 52 sec per photo (Borderless) ESC/P-R	
Printer Language	ESC/P-R	
Automatic 2-sided printing	Yes (up to A3)	
Copying		
Copy Speed ISO 29183, A4 (Black / Colour)		
ISO 29183, A4 (Black / Colour)	N/A	Simplex: Up to 16ipm / 8.8ipm
Maximum Copies from Standalone Reduction / Enlargement	N/A N/A	999 copies 25 - 400%, Auto Fit Function
Maximum Copy Resolution	N/A	600 x 1200dpi
Maximum Copy Size	N/A	A3
Scanning	-	<del></del>
Scanner Type	N/A	Flatbed Colour Image Scanner
Sensor Type	N/A	CIS
Optical Resolution	N/A	1200 x 2400 dpi
Maximum Scan Area Scanner Bit Depth	N/A	297.18 x 431.8 mm (11.7 x 17")
Colour	N/A	48-bit input, 24-bit output
Grayscale	N/A	16-bit input, 8-bit output
Black & White	N/A	16-bit input, 1-bit output
Scan Speed		
Flatbed / ADF (Simplex) Monochrome 200dpi	N/A	6.0sec / 11.0ppm
Colour 200dpi	N/A	12sec / 5.5ppm
Fax Function		
Type of Fax	N/A	Walk-up Black-and-white and Colour Fax Capability
Receive Memory / Page Memory	N/A	6MB / Page Memory up to 550 pages (ITU-T No.1 chart)
		(ITU-T No.1 chart)
Error Correction Mode Fax Speed (Data Transfer Rate)	N/A N/A	ITU Group3 Fax with Error Correction Mode Up to 33.6kbps, Approx. 3sec/page
Fax Resolution	N/A	Up to 200 x 200 dpi
Receiving Paper Size	N/A	A5, Half Letter, B5(JIS), Letter, A4, Legal, B4(JIS), A3, 11" x 17"
		11" x 17"
Speed Dial / Group Dial	N/A	Up to 200 numbers / Up to 199 groups
Fax Features	N/A	PC Fax (Transmission / Receive), Automatic Redial, Address Book, Delay Send, Transmit Reservation
		(100 case), Broadcast Fax (Mono Only)
ADF Function	•	
Support Paper Thickness	N/A	64-95 g/m <sup>2</sup>
Paper Capacity	N/A	35 pages (80g/m²)
Automatic 2-sided Functions	N/A	Scan, Copy and Fax
USB Host Function USB Host	N/A	USB Host (Scan to Memory Device / Storage Function)
Type of Direct Printing	N/A	USB Memory
Paper Handling		
Paper Feed Method	Friction Feed	
Number of Paper Trays	3 (Front 2, Rear 1)	2 (Front 1, Rear 1)
Paper Hold Capacity		
Input Capacity	Cassette 1: 250 sheets (80g/m²)	Cassette 1: 250 sheets (80g/m²) Rear Slot: 1 sheet
	Rear Slot: 1 sheet	rical Giot. I Street
Output Capacity	Cassette 2: 250 sheets (80g/m²) Rear Slot: 1 sheet 125 sheets (80 g/m²)	
Paper Size	125 sheets (80 a/m²)	
Paper Size Maximum Paper Size	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24")	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"
Paper Size Maximum Paper Size Print Margin	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24")	
Paper Size Maximum Paper Size Print Margin Interface USB	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custe	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) 13
Paper Size Maximum Paper Size Print Margin Interface USB Network	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custe	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) 13
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custe	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) 13
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocols	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via cust USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA,	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custe	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) " -Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD ILlmit Access Function. PIN No. Certification.
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via cust USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA,	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocols	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95* x 47.24*) 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPv4, TCP/IPv6, LPP, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD  Limit Access Function, PIN No. Certification,  LDAP Address Book, Panel Admin Mode
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95* x 47.24*) 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SNMP, HTTP, DHCP BOOTP, APIPA, Panel Admin Mode Epson iPrint, Epson Email Print, Remote Print, Driver	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "3  -FI Direct, NFC "9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No. Certification, LDAP Address Book, Panel Admin Mode  Epson IPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocols Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95* x 47.24*) 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPv4, TCP/IPv6, LPP, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "3  -FI Direct, NFC "9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No. Certification, LDAP Address Book, Panel Admin Mode  Epson IPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode Epson iPrint, Epson Email Print, Remote Print, Driver Apple AirPrint, Google Cloud Print, M	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) " -Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD LImit Access Function, PIN No. Certification, LDAP Address Book, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Interface Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95* x 47.24*) 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SNMP, HTTP, DHCP BOOTP, APIPA, Panel Admin Mode Epson iPrint, Epson Email Print, Remote Print, Driver	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "3  -FI Direct, NFC "9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No. Certification, LDAP Address Book, Panel Admin Mode  Epson IPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LP0, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Interface Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen	125 sheets (80 g/m²) A3+, A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LP0, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPV4, TCP/IPV6, LPD, IPP, PORT SNMR, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPV4, TCP/IPV6, LPD, IPP, PORT SIMP, HTTP, DHCP BOOTP, APIPA, Pandle Admin Mode Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/m, Wi TCP/IPA, TCP/IPA, LPD, IPP, DRT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AliPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 106.8 or later  AC 220 - 240 V	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, W TCP/IPV4, TCP/IPV6, LPD, IPP, PORT SIMP, HTTP, DHCP BOOTP, APIPA, Pandle Admin Mode Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC 9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD Limit Access Function, PIN No, Certification, LDAP Address Book, Panel Admin Mode Epson IPint, Epson Email Print, Remote Print Driver, Scan to Cloud lopria Print Service  14.3" TFT Colour LCD
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/m, Wi TCP/IPA, TCP/IPA, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AliPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 106.8 or later  AC 220 - 240 V 50 - 60 Hz	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD   Limit Access Function, PIN No. Certification,  LDAP Address Book, Panel Admin Mode    Epson iPrint, Epson Email Print, Remote Print Driver,   Scan to Cloud     Comparable of the Print Colour LCD  Windows Server 2003 / 2008 / 2012 / 2016   I for Windows Server OS
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/m, Wi TCP/IPA, TCP/IPA, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AliPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 106.8 or later  AC 220 - 240 V 50 - 60 Hz	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13" om settings in printer driver (except plain paper) "  Fi Direct, NFC "9100, WSD PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD   Limit Access Function, PIN No. Certification,   LDAP Address Book, Panel Admin Mode   Epson iPrint, Epson Email Print, Remote Print Driver,   Scan to Cloud     Scan to Cloud   14.3" TFT Colour LCD   Windows Server 2003 / 2008 / 2012 / 2016     Ifor Windows Server OS
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/m, Wi TCP/IPA, TCP/IPA, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AliPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 106.8 or later  AC 220 - 240 V 50 - 60 Hz	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD   Limit Access Function, PIN No. Certification,  LDAP Address Book, Panel Admin Mode    Epson iPrint, Epson Email Print, Remote Print Driver,   Scan to Cloud     Comparable of the Print Colour LCD  Windows Server 2003 / 2008 / 2012 / 2016   I for Windows Server OS
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LOB Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power of Po	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPv4, TCP/IPv6, LPD, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later  AC 220 - 240 V 50 - 60 Hz  20W 5.2W 5.2W 5.2W 5.2W 5.2W 5.2B - 220 - 240 V 5.2W 5.2W 5.2W 5.2W 5.2B - 250 - 250 F	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD  [Limit Access Function, PIN No. Certification,
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Epson DURABrite Ultra Ink	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPV4, TCP/IPV6, LPD, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later  AC 220 - 240 V 50 - 60 Hz  20W 5.2W 0.8W 0.8W 0.9W Page Yield"	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "3  -Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD    Limit Access Function, PIN No. Certification,   LDAP Address Book, Panel Admin Mode    Epson iPrint, Epson Email Print, Remote Print Driver,   Scan to Cloud     Copris Print Service   4.3" TFT Colour LCD  Windows Server 2003 / 2008 / 2012 / 2016     for Windows Server OS    18W   8.5W   1.0W   0.2W     0.2W   0.2W   0.00   0.00   0.00     OZW   0.00   0.00     OZW   0.00   0.00     OZW   0.00   0.00   0.00     O
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Epson DURABrite Ultra Ink Black	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPVA, TCP/IPV6, LPD, IPP, PORT SNMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AlrPrint, Google Cloud Print, M 2.2" Mono LCD  Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later  AC 220 - 240 V 50 - 60 Hz 20W 5.5 W 0.8W 0.8W 0.2W	atter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD  [Limit Access Function, PIN No. Certification,
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Management Protocols Security Functions  Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Epson DURABrite Ultra Ink Black	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPV4, ICP/IPV6, LPD, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later  AC 220 - 240 V 50 - 60 Hz  20W 5.2W 0.8W 0.2W Page Yield" 2,200 pages	etter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "3  -Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD    Limit Access Function, PIN No. Certification,   LDAP Address Book, Panel Admin Mode    Epson iPrint, Epson Email Print, Remote Print Driver,   Scan to Cloud     Copria Print Service   4.3" TFT Colour LCD  Windows Server 2003 / 2008 / 2012 / 2016   for Windows Server OS    18W   8.5W   1.0W     0.2W   Order Code     C13T188190   C13T188290
Paper Size Maximum Paper Size Print Margin Interface USB Network Network Protocol Network Protocol Network Protocol Security Functions Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility  Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Epson DURABrite Ultra Ink Black	125 sheets (80 g/m²) A3+ A3, A4, A5, A6, B4, B5, Legal, L 329 x 1200 mm (12.95" x 47.24") 0 mm top, left, right, bottom via custs USB 2.0 0 mm top, left, right, bottom via custs USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi TCP/IPV4, TCP/IPV6, LPD, IPP, PORT SIMP, HTTP, DHCP, BOOTP, APIPA, Panel Admin Mode  Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, M 2.2" Mono LCD Windows XP / Vista / 7 / 8 / 8.1 / 10, Only printing functions are supported Mac OS X 10.6.8 or later  AC 220 - 240 V 50 - 60 Hz  20W 5.2W 0.8W 0.8W 0.9W Page Yield"	atter, 5x7", 4x6", Envelopes: #10, DL, C6, C4, 8.5x13"  om settings in printer driver (except plain paper) "  Fi Direct, NFC  9100, WSD  PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD  [Limit Access Function, PIN No. Certification,

Dimensions & Weight

WF-7211 Weight: 15.5kg (34.2lb)



WF-7711 Weight: 18.7 kg (41.2lb)



\*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



Paper.





Black Text

#2 Black Text and graphic

\*2 When printed on Epson Premium Glossy Photo

\*3 Otherwise 3mm top, left, right and bottom.

\*4 In accordance with ISO 24711/24712. Actual yields will vary considerably for reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour.

A variable amount of ink remains in the cartridges after the "replace cartridge" signal. Part of the ink from the first cartridges is used for priming the printer. Ink is used for both printing and print head maintenance. All inks are used for both black and colour printing.

© 2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.
EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S and other countries. App Store is a service mark of Apple Inc.