

Product Specifications

FlashCheck Lollipop Auto Cal Min/Max Antimicrobial Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±0.9°F from -40°F to +14°F (±0.5°C from -40°C to -10°C) ±0.5°F from +14°F to +68°F (±0.3°C from -10°C to +20°C) ±0.9°F from +69°F to +239°F (±0.5°C from +21°C to +115°C) ±1.8°F from 240°F to +311°F (±1.0°C from 116°C to 155°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	1 second
Display Window Size	1.3in W x 0.9in H (32.9mm W x 22.9mm H)
Calibration	Automatic calibration feature
Battery	Button cell alkaline
Body Casing	ABS plastic with antimicrobial additive
Probe Length	4.13in (105mm)
Probe Diameter	0.14in (3.56mm), reduced tip 0.1in (2.5mm)
Weight	1.3oz (37.6g)
Waterproof Rating	IP65
Factory Calibration	NIST traceable calibration certified
Compliance Certificate	Manufacturers certificate of compliance available from DeltaTrak, NIST Traceable, NSF, CE



Model 11050

- Antimicrobial additive inhibits growth of bacteria, mould and fungus
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Sealed unibody construction
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B))
- NSF certified
- °F/°C selectable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



SS 11050 21L2

