## **Product Specifications**

## FlashCheck. Needle Probe Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Accuracy	$\begin{array}{l} \pm 0.9^{\circ}\text{F from } -40^{\circ}\text{F to } +14^{\circ}\text{F} \\ (\pm 0.5^{\circ}\text{C from } -40^{\circ}\text{C to } -10^{\circ}\text{C}) \\ \pm 0.5^{\circ}\text{F from } +14^{\circ}\text{F to } +68^{\circ}\text{F} \\ (\pm 0.3^{\circ}\text{C from } -10^{\circ}\text{C to } +20^{\circ}\text{C}) \\ \pm 0.9^{\circ}\text{F from } +69^{\circ}\text{F to } +122^{\circ}\text{F} \\ (\pm 0.5^{\circ}\text{C from } +21^{\circ}\text{C to } +50^{\circ}\text{C}) \\ \pm 1.8^{\circ}\text{F from } +123^{\circ}\text{F to } +311^{\circ}\text{F} \\ (\pm 1.0^{\circ}\text{C from } +51^{\circ}\text{C to } +155^{\circ}\text{C}) \end{array}$
Resolution	0.1°F (0.1°C)
Display Reading Update	Every 2 seconds
Display Window Size	1.5in W x 0.5in H (38mm W x 12.7mm H)
Probe	Stainless steel needle tip probe, dia 0.1in (2.5mm), Probe stem length 3.90in (99mm)
Body	ABS plastic
Calibration	Factory calibrated to NIST traceable standards
Battery	1.5V button
Battery Saver	Automatic shut off after 10 minutes
IP Rating	IP56 rated
Compliance Certificate	NSF, RoHS-compliant device and NIST traceable HACCP tool

## Model 11089-01

- Reduced tip ideal for measuring temperature of thin mass foods such as meat patties, chicken and fish fillets, per FDA Food Code 4-302.12 (B)
- Needle tip provides extremely fast response time
- °C/°F switchable scale at the touch of a button
- Pocket clip for portability

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



SS 11089-01 22D2