

YTP38Z1/YTP45Z1

- ◆ ✘ IC driver ◆ ✘ Big beam angle
- ◆ ✘ Serialized design, simple and beautiful
- ◆ ✘ Plastic + aluminum heat sink
- ◆ ✘ High transmittance PC cover
- ◆ ✘ High quality 2835LED chips
- ◆ ✘ Comply with LVD, Safe and reliable



Type	Watts	Voltage	PF	Luminous Flux 3000K/4000K&6500K	Beam Angle	CRI	Dimension (mm)	Cap	Lifetime (h)	Quantity
YTP38Z1	10W	220-240V	0.5	720lm/810lm	200°	≥80	Ø38*118	E27	15000	100/ctn
YTP38B1	10W	220-240V	0.5	720lm/810lm	200°	≥80	Ø38*118	PLC	15000	100/ctn
YTP45Z1	15W	220-240V	0.5	1200lm/1350lm	200°	≥80	Ø45*143	E27	15000	100/ctn
YTP45B1	15W	220-240V	0.5	1200lm/1350lm	200°	≥80	Ø45*143	PLC	15000	100/ctn
YTP38Z1 (3IN1)	10W	220-240V	0.5	720lm/810lm	200°	≥80	Ø38*118	E27	15000	10/ctn

E S L LIGHTING (M) SDN BHD (746428-A)

No. 19, 19-1, 19-2, Jalan PDR 6, Kawasan Perniagaan Desa Ria, 43300 Balakong, Seri Kembangan, Selangor.

Tel: 03-8961 2308 Fax: 03-8961 2305

Website: www.esllighting.com.my



Warm White
3000K



Cool White
4000K



Day Light
6500K