

YTPDGLE5

- ◆ ✘ IC driver
- ◆ ✘ Big beam angle
- ◆ ✘ Die-cast aluminum heat sink
- ◆ ✘ High transmittance PC cover
- ◆ ✘ High quality 2835LED chips
- ◆ ✘ Comply with LVD, Safe and reliable



REFLECTOR

Type	Watts	Voltage	PF	Luminous Flux 3000K/6500K	Beam Angle	CRI	Dimension (mm)	Cap	Lifetime (h)	Quantity
YTPDGLE5	50W	100-240V	0.5	4000/4500lm	200°	≥80	Ø118*155	E27	25000	20/ctn
	70W	100-240V	0.9	7000lm	200°	≥80	Ø138*205	E27/ E40	25000	20/ctn
	100W	100-240V	0.9	10000lm	200°	≥80	Ø138*230		25000	8/ctn
REFLECTOR	Suitable size 50W	Color: WHITE								20/ctn

E S L LIGHTING (M) SDN BHD (746428-A)

No. 19, 19-1, 19-2, Jalan PDR 6, Kawasan Perniagaan Desa Ria, 43300 Balakong, Seri Kembangan, Selangor.

Tel: 03-8961 2308 Fax: 03-8961 2305

Website: www.esllighting.com.my

50W = Daylight / Warm White
70W, 100W = Daylight

