

MQTL1119-F

- ◆ ※ Embedded installation
- ◆ ※ Drive built-in, integrated design
- ◆ ※ High luminous flux, high luminous efficiency
- ◆ ※ Back lit
- ◆ ※ High quality 2835 LED chips
- ◆ ※ Comply with LVD, Safe and reliable



Type	Watts	Voltage	PF	Luminous Flux 3000K&4000K&6500K	Beam Angle	CRI	Dimension (mm)	Hold (mm)	Lifetime (h)	Quantity
MQTL1119-F	9W	220-240V	0.5	650/720lm	120°	≥80	125*125*30 4"	105*105	15000	60/ctn
MQTL1119-F	12W	220-240V	0.5	870/960lm	120°	≥80	145*145*30 5"	125*125	15000	30/ctn
MQTL1119-F	15W	220-240V	0.5	1080/1200lm	120°	≥80	175*175*30 6"	150*150	15000	30/ctn
MQTL1119-F	24W	220-240V	0.5	1580/1760lm	120°	≥80	225*225*30 8"	200*200	15000	24/ctn

E S L LIGHTING (M) SDN BHD (746428-A)

No. 19, 19-1, 19-2, Jalan PDR 6, Kawasan Perniagaan Desa Ria, 43300 Balakong, Seri Kembangan, Selangor.

Tel: 03-8961 2308 Fax: 03-8961 2305

Website: www.esllighting.com.my



Warm White
3000K



Cool White
4000K



Day Light
6500K