

# BSLight



## LED T8 Tube Series



### APPLICATION




Widely applied in factories, offices, banks, shopping centres, subways, schools and other places with high brightness and energy saving benefits.



### FEATURES

- Perfect for replacement of traditional fluorescent tubes.
- 360 degree full direction lighting.
- Built-in driver supplies with no compromise on stability and life warranty.
- Double ended input for choice.
- Life Time 15,000 hours and above.



Model	Power (W)	Size	Voltage	CCT (K)	Lumen (lm)	CRI
<b>BSL (Non-SIRIM Available)</b>						
BSL-LED-11W	11	2 ft	AC185-265V	6500K	1100lm	≥ 80
BSL-LED-22W	22	4 ft	AC185-265V	6500K	2200lm	≥ 80
BSL-LED-30W	30	4 ft	AC165-265V	6500K	3200lm	≥ 80
<b>BSLight eco </b>						
ECO-T8-10W	10	2 ft	AC220-240V	3000/4000/6500K	900lm	≥ 80
ECO-T8-20W	20	4 ft	AC220-240V	3000/4000/6500K	1920lm	≥ 80
<b>BSLight </b>						
BSL-LED30W	30	4 ft	AC220-240V	6500K	3500lm	≥ 80
<b>BSLight NANO </b>						
NANO-T8-10W	10	2 ft	AC220-240V	6500K	780lm	≥ 80
NANO-T8-20W	20	4 ft	AC220-240V	6500K	1650lm	≥ 80
<b>BSLight Color Tube</b>						
IP65-T8-10W	10	2 ft	AC220-265V	R/G/B/Y/3000/6500K		
IP65-T8-18W	18	4 ft	AC220-265V	R/G/B/Y/3000/6500K		
COL-T8-20W (Glass)	20	4 ft	AC220-240V	R/G/B/Y		

### CONNECTION METHOD:

